

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	02 Hour 42 Min 30 Sec
Total Counter :	700594	Total Running Time :	2409 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.77	kN	No		
HEP :	20.0 %	22.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.39	kN	Yes 15	Times	
Ref :		19.01	kN			
LCP :	2.0 %	18.63	kN	Yes 15	Times	
LEP :	20.0 %	15.21	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.26	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.74	kN	Min :	1.63	kN	Punch NO.;	8
SD :	1.50	%	Max :	1.80	kN	Punch NO.;	68
Mean Main Pressure :	18.98	kN	Min :	15.87	kN	Punch NO.;	8
SD :	3.70	%	Max :	20.27	kN	Punch NO.;	75
Filling Depth :	Increase ; 8	Times	Decrease ; 13	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.51	mm
Filling Depth :	8.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.58	kN		
	Max ;	0.86	kN	Max Punch ;	28
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.28	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700594	Tablets			
A.W.C Counter :	696539	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	696018 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	02 Hour 42 Min 30 Sec
Total Counter :	700594	Total Running Time :	2409 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	25.97	kN	No		
HEP :	20.0 %	24.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.19	kN	Yes 15	Times	
Ref :		20.77	kN			
LCP :	2.0 %	20.36	kN	Yes 15	Times	
LEP :	20.0 %	16.62	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	15.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.94	kN	Punch NO.;	12
SD :	1.10	%	Max :	2.04	kN	Punch NO.;	6
Mean Main Pressure :	21.32	kN	Min :	19.75	kN	Punch NO.;	18
SD :	3.20	%	Max :	23.04	kN	Punch NO.;	75
Filling Depth :	Increase ;	8	Times	Decrease ;	23	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.67	mm	Main Thickness ;	2.67	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.59	kN		
	Max ;	0.85	kN	Max Punch ;	30
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.28	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700594	Tablets			
A.W.C Counter :	696539	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	696018 (99.9%)	Tablets			