

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2503910
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 49 Sec
Total Counter :	1351014	Total Running Time :	2423 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.38	kN	No		
HEP :	20.0 %	23.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.90	kN	Yes 15	Times	
Ref :		19.51	kN			
LCP :	2.0 %	19.12	kN	Yes 15	Times	
LEP :	20.0 %	15.61	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.63	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.72	kN	Punch NO.;	8
SD :	1.10	%	Max :	1.83	kN	Punch NO.;	60
Mean Main Pressure :	19.61	kN	Min :	17.80	kN	Punch NO.;	58
SD :	2.80	%	Max :	20.94	kN	Punch NO.;	75
Filling Depth :	Increase ; 33	Times	Decrease ; 59	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	2.55	mm
Filling Depth :	8.14	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.49	kN		
	Max ;	0.62	kN	Max Punch ;	52
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1351014	Tablets			
A.W.C Counter :	1347344	Tablets			
HEP :	27 (0.0%)	Tablets	LEP :	13 (0.0%)	Tablets
GOOD :	1347304 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2503910
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 49 Sec
Total Counter :	1351014	Total Running Time :	2423 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.55	kN	No		
HEP :	20.0 %	22.61	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.22	kN	Yes 15	Times	
Ref :		18.84	kN			
LCP :	2.0 %	18.47	kN	Yes 15	Times	
LEP :	20.0 %	15.07	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.88	kN	Punch NO.;	11
SD :	1.00	%	Max :	1.98	kN	Punch NO.;	60
Mean Main Pressure :	18.74	kN	Min :	17.20	kN	Punch NO.;	18
SD :	3.70	%	Max :	21.35	kN	Punch NO.;	60
Filling Depth :	Increase ;	25	Times	Decrease ;	105	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.78	mm
Filling Depth :	8.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.49	kN		
	Max ;	0.63	kN	Max Punch ;	67
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1351014	Tablets			
A.W.C Counter :	1347344	Tablets			
HEP :	27 (0.0%)	Tablets	LEP :	13 (0.0%)	Tablets
GOOD :	1347304 (100.0%)	Tablets			