

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	10 Hour 43 Min 49 Sec
Total Counter :	2769172	Total Running Time :	2451 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.71	kN	No		
HEP :	20.0 %	23.72	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.16	kN	Yes 15	Times	
Ref :		19.77	kN			
LCP :	2.0 %	19.37	kN	Yes 15	Times	
LEP :	20.0 %	15.81	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.83	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.65	kN	Min :	1.59	kN	Punch NO.;	27
		1.40	%	Max :	1.71	kN	Punch NO.;	10
Mean Main Pressure :	SD :	19.70	kN	Min :	17.98	kN	Punch NO.;	27
		2.90	%	Max :	21.01	kN	Punch NO.;	60
Filling Depth :	Increase ;	30	Times	Decrease ;	41	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.53	mm	Main Thickness ;	2.54	mm
Filling Depth :	8.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.71	kN		
	Max ;	0.87	kN	Max Punch ;	57
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2769172	Tablets			
A.W.C Counter :	2761464	Tablets			
HEP :	133 (0.0%)	Tablets	LEP :	266 (0.0%)	Tablets
GOOD :	2761065 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	10 Hour 43 Min 49 Sec
Total Counter :	2769172	Total Running Time :	2451 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	66	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.15	kN	No		
HEP :	20.0 %	26.07	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.16	kN	Yes	15	Times
Ref :		21.72	kN			
LCP :	2.0 %	21.29	kN	Yes	15	Times
LEP :	20.0 %	17.38	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	16.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.80	kN	Punch NO.;	49
SD :	1.20	%	Max :	1.89	kN	Punch NO.;	67
Mean Main Pressure :	21.99	kN	Min :	20.59	kN	Punch NO.;	18
SD :	4.40	%	Max :	25.33	kN	Punch NO.;	60
Filling Depth :	Increase ;	27	Times	Decrease ;	48	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.816	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.70	kN		
	Max ;	0.85	kN	Max Punch ;	57
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2769172	Tablets			
A.W.C Counter :	2761541	Tablets			
HEP :	133 (0.0%)	Tablets	LEP :	266 (0.0%)	Tablets
GOOD :	2761142 (100.0%)	Tablets			