

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	01 Hour 08 Min 35 Sec
Total Counter :	150076	Total Running Time :	2453 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.36	kN	No		
HEP :	20.0 %	14.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.53	kN	Yes 15	Times	
Ref :		12.29	kN			
LCP :	2.0 %	12.04	kN	Yes 15	Times	
LEP :	20.0 %	9.83	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.30	kN	Punch NO.;	14
SD :	5.40	%	Max :	1.67	kN	Punch NO.;	7
Mean Main Pressure :	12.33	kN	Min :	11.93	kN	Punch NO.;	45
SD :	1.80	%	Max :	13.04	kN	Punch NO.;	53
Filling Depth :	Increase ; 1	Times	Decrease ;	11	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.00	mm
Filling Depth :	8.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	5
Ejection Force :	Average ;	1.73	kN		
	Max ;	1.78	kN	Max Punch ;	42

Tablet Data (N/A)

Total Counter :	150076	Tablets			
A.W.C Counter :	135317	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	135308 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	01 Hour 08 Min 35 Sec
Total Counter :	150076	Total Running Time :	2453 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	81	%	Manual ;	21	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.76	kN	No		
HEP :	20.0 %	16.09	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.67	kN	Yes 15	Times	
Ref :		13.41	kN			
LCP :	2.0 %	13.14	kN	Yes 15	Times	
LEP :	20.0 %	10.72	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.05	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.43	kN	Min :	1.27	kN	Punch NO.;	35
SD :	5.80	%	Max :	1.62	kN	Punch NO.;	48
Mean Main Pressure :	13.46	kN	Min :	12.85	kN	Punch NO.;	19
SD :	2.60	%	Max :	14.46	kN	Punch NO.;	35
Filling Depth :	Increase ;	10	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.10	mm
Filling Depth :	8.00	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	5
Ejection Force :	Average ;	1.74	kN		
	Max ;	1.79	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	150076	Tablets			
A.W.C Counter :	135317	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	135308 (100.0%)	Tablets			