

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	00 Hour 56 Min 26 Sec
Total Counter :	3194422	Total Running Time :	2477 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.96	kN	No		
HEP :	20.0 %	15.32	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.02	kN	Yes 15	Times	
Ref :		12.77	kN			
LCP :	2.0 %	12.51	kN	Yes 15	Times	
LEP :	20.0 %	10.21	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.37	kN	Min :	2.10	kN	Punch NO.;	5
		5.90	%	Max :	2.92	kN	Punch NO.;	11
Mean Main Pressure :	SD :	12.79	kN	Min :	12.39	kN	Punch NO.;	28
		2.10	%	Max :	14.05	kN	Punch NO.;	24
Filling Depth :	Increase ;	7	Times	Decrease ;	10	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.01	mm	Main Thickness ;	3.01	mm
Filling Depth :	7.85	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	35
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	5
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	3194422	Tablets			
A.W.C Counter :	3175400	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	3175382 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	00 Hour 56 Min 26 Sec
Total Counter :	3194422	Total Running Time :	2477 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	87	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.66	kN	No		
HEP :	20.0 %	16.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.60	kN	Yes 15	Times	
Ref :		13.33	kN			
LCP :	2.0 %	13.06	kN	Yes 15	Times	
LEP :	20.0 %	10.66	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.00	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.02	kN	Punch NO.;	15
SD :	4.60	%	Max :	2.49	kN	Punch NO.;	4
Mean Main Pressure :	13.15	kN	Min :	12.57	kN	Punch NO.;	28
SD :	2.40	%	Max :	13.92	kN	Punch NO.;	49
Filling Depth :	Increase ;	47	Times	Decrease ;	46	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	35
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	5
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	3194422	Tablets			
A.W.C Counter :	3175400	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	3175382 (100.0%)	Tablets			