

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sp98936	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	01 Hour 04 Min 36 Sec
Total Counter :	150068	Total Running Time :	2488 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.77	kN	No		
HEP :	20.0 %	16.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.69	kN	Yes 15	Times	
Ref :		13.42	kN			
LCP :	2.0 %	13.15	kN	Yes 15	Times	
LEP :	20.0 %	10.74	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.59	kN	Min :	3.31	kN	Punch NO.;	38
SD :	4.60	%	Max :	3.97	kN	Punch NO.;	13
Mean Main Pressure :	13.40	kN	Min :	13.02	kN	Punch NO.;	45
SD :	1.60	%	Max :	14.04	kN	Punch NO.;	53
Filling Depth :	Increase ; 81	Times	Decrease ;	34	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	8.49	mm	Current Cam :	Cam C	
Main Air pressure :	0.708	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	32
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	150068	Tablets			
A.W.C Counter :	143843	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	143843 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sp98936	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	01 Hour 04 Min 36 Sec
Total Counter :	150068	Total Running Time :	2488 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	17.22	kN	No		
HEP :	20.0 %	16.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.05	kN	Yes 15	Times	
Ref :		13.78	kN			
LCP :	2.0 %	13.50	kN	Yes 15	Times	
LEP :	20.0 %	11.02	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.27	kN	Min :	3.01	kN	Punch NO.;	21
SD :	4.00	%	Max :	3.59	kN	Punch NO.;	43
Mean Main Pressure :	13.62	kN	Min :	12.89	kN	Punch NO.;	44
SD :	2.70	%	Max :	14.65	kN	Punch NO.;	39
Filling Depth :	Increase ;	118	Times	Decrease ;	139	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.06	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.708	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	32
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	150068	Tablets			
A.W.C Counter :	143843	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	143843 (100.0%)	Tablets			