

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	17 Hour 34 Min 57 Sec
Total Counter :	3051416	Total Running Time :	2505 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		220	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		300	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.88	kN	No		
HEP :	20.0 %	16.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.78	kN	Yes 15	Times	
Ref :		13.51	kN			
LCP :	2.0 %	13.24	kN	Yes 15	Times	
LEP :	20.0 %	10.81	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.65	kN	Min :	2.35	kN	Punch NO.;	31
SD :	5.60	%	Max :	3.11	kN	Punch NO.;	11
Mean Main Pressure :	13.61	kN	Min :	12.83	kN	Punch NO.;	42
SD :	2.90	%	Max :	14.67	kN	Punch NO.;	53
Filling Depth :	Increase ;	108	Times	Decrease ;	75	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	7.92	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	143	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	48
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	3051416	Tablets			
A.W.C Counter :	3042738	Tablets			
HEP :	151 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	3042387 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	17 Hour 34 Min 57 Sec
Total Counter :	3051416	Total Running Time :	2505 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		220	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		300	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	19.88	kN	No		
HEP :	20.0 %	19.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.22	kN	Yes 15	Times	
Ref :		15.90	kN			
LCP :	2.0 %	15.58	kN	Yes 15	Times	
LEP :	20.0 %	12.72	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	11.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.68	kN	Min :	2.36	kN	Punch NO.;	31
		4.90	%	Max :	3.03	kN	Punch NO.;	4
Mean Main Pressure :	SD :	16.07	kN	Min :	14.90	kN	Punch NO.;	28
		2.90	%	Max :	17.27	kN	Punch NO.;	49
Filling Depth :	Increase ;	251	Times	Decrease ;	254	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.75	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	143	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	5
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	3051416	Tablets			
A.W.C Counter :	3042738	Tablets			
HEP :	151 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	3042387 (100.0%)	Tablets			