

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	cb83530	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	00 Hour 35 Min 33 Sec
Total Counter :	50020	Total Running Time :	2514 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.09	kN	No		
HEP :	23.0 %	12.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.43	kN	Yes 15	Times	
Ref :		10.23	kN			
LCP :	2.0 %	10.02	kN	Yes 15	Times	
LEP :	23.0 %	7.88	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.37	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.57	kN	Min :	1.55	kN	Punch NO.;	32
SD :	0.70	%	Max :	1.61	kN	Punch NO.;	19
Mean Main Pressure :	10.63	kN	Min :	9.70	kN	Punch NO.;	36
SD :	4.40	%	Max :	11.74	kN	Punch NO.;	32
Filling Depth :	Increase ; 223	Times	Decrease ;	201	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	28	Min			
Lower Punch Remain Time (S2):	58	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	16
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50020	Tablets			
A.W.C Counter :	48866	Tablets			
HEP :	179 (0.4%)	Tablets	LEP :	105 (0.2%)	Tablets
GOOD :	48582 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	cb83530	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	00 Hour 35 Min 33 Sec
Total Counter :	50020	Total Running Time :	2514 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	12.20	kN	No		
HEP :	23.0 %	11.72	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.72	kN	Yes 15	Times	
Ref :		9.53	kN			
LCP :	2.0 %	9.34	kN	Yes 15	Times	
LEP :	23.0 %	7.34	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	6.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.23	kN	Min :	1.20	kN	Punch NO.;	2
SD :	1.00	%	Max :	1.26	kN	Punch NO.;	1
Mean Main Pressure :	9.41	kN	Min :	8.32	kN	Punch NO.;	49
SD :	5.40	%	Max :	10.18	kN	Punch NO.;	31
Filling Depth :	Increase ; 379	Times	Decrease ;	378	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	8.14	mm	Current Cam :	Cam C	
Main Air pressure :	0.753	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	28	Min			
Lower Punch Remain Time (S2):	58	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	41
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50020	Tablets			
A.W.C Counter :	48866	Tablets			
HEP :	179 (0.4%)	Tablets	LEP :	105 (0.2%)	Tablets
GOOD :	48582 (99.4%)	Tablets			