

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	cb83530	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	05 Hour 42 Min 30 Sec
Total Counter :	700262	Total Running Time :	2519 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.94	kN	No		
HEP :	23.0 %	13.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.11	kN	Yes 15	Times	
Ref :		10.89	kN			
LCP :	2.0 %	10.68	kN	Yes 15	Times	
LEP :	23.0 %	8.39	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.54	kN	Min :	1.52	kN	Punch NO.;	22
SD :	0.40	%	Max :	1.56	kN	Punch NO.;	20
Mean Main Pressure :	11.11	kN	Min :	10.07	kN	Punch NO.;	52
SD :	5.30	%	Max :	12.53	kN	Punch NO.;	8
Filling Depth :	Increase ; 872	Times	Decrease ;	855	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.08	mm	Main Thickness ;	3.08	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	71	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	31
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700262	Tablets			
A.W.C Counter :	699011	Tablets			
HEP :	829 (0.1%)	Tablets	LEP :	107 (0.0%)	Tablets
GOOD :	698075 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	cb83530	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	05 Hour 42 Min 30 Sec
Total Counter :	700262	Total Running Time :	2519 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	138	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	12.83	kN	No		
HEP :	23.0 %	12.33	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.23	kN	Yes 15	Times	
Ref :		10.03	kN			
LCP :	2.0 %	9.83	kN	Yes 15	Times	
LEP :	23.0 %	7.72	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.17	kN	Min :	1.14	kN	Punch NO.;	6
SD :	1.20	%	Max :	1.21	kN	Punch NO.;	1
Mean Main Pressure :	10.13	kN	Min :	9.14	kN	Punch NO.;	52
SD :	4.20	%	Max :	11.24	kN	Punch NO.;	6
Filling Depth :	Increase ; 790	Times	Decrease ;	789	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	8.27	mm	Current Cam :	Cam C	
Main Air pressure :	0.790	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	71	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	31
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700262	Tablets			
A.W.C Counter :	699011	Tablets			
HEP :	829 (0.1%)	Tablets	LEP :	107 (0.0%)	Tablets
GOOD :	698075 (99.9%)	Tablets			