

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	rp98927	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	11 Hour 47 Min 32 Sec
Total Counter :	1401548	Total Running Time :	2526 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.94	kN	No		
HEP :	23.0 %	13.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.11	kN	Yes 15	Times	
Ref :		10.89	kN			
LCP :	2.0 %	10.68	kN	Yes 15	Times	
LEP :	23.0 %	8.39	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.55	kN	Min :	1.53	kN	Punch NO.;	44
SD :	0.50	%	Max :	1.58	kN	Punch NO.;	53
Mean Main Pressure :	11.68	kN	Min :	9.79	kN	Punch NO.;	53
SD :	6.00	%	Max :	13.06	kN	Punch NO.;	23
Filling Depth :	Increase ; 692	Times	Decrease ;	691	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.08	mm	Main Thickness ;	3.08	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.731	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	77	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1401548	Tablets			
A.W.C Counter :	1397158	Tablets			
HEP :	1529 (0.1%)	Tablets	LEP :	107 (0.0%)	Tablets
GOOD :	1395522 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo200mg STUB3D00
User ID :	rp98927	Batch NO. :	UBM2500320
Print Interval :	50000 Tablets	Running Time :	11 Hour 47 Min 32 Sec
Total Counter :	1401548	Total Running Time :	2526 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	138	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	12.83	kN	No		
HEP :	23.0 %	12.33	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.23	kN	Yes 15	Times	
Ref :		10.03	kN			
LCP :	2.0 %	9.83	kN	Yes 15	Times	
LEP :	23.0 %	7.72	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.16	kN	Min :	1.13	kN	Punch NO.;	27
SD :	1.20	%	Max :	1.20	kN	Punch NO.;	19
Mean Main Pressure :	9.83	kN	Min :	8.91	kN	Punch NO.;	52
SD :	5.10	%	Max :	11.07	kN	Punch NO.;	7
Filling Depth :	Increase ; 392	Times	Decrease ;	389	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.34	mm	Main Thickness ;	3.34	mm
Filling Depth :	8.24	mm	Current Cam :	Cam C	
Main Air pressure :	0.731	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	77	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1401548	Tablets			
A.W.C Counter :	1397158	Tablets			
HEP :	1529 (0.1%)	Tablets	LEP :	107 (0.0%)	Tablets
GOOD :	1395522 (99.9%)	Tablets			