

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503150
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 17 Sec
Total Counter :	2952162	Total Running Time :	2538 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	18.94	kN	No		
HEP :	23.0 %	18.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.09	kN	Yes 15	Times	
Ref :		14.79	kN			
LCP :	2.0 %	14.50	kN	Yes 15	Times	
LEP :	23.0 %	11.39	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	10.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.79	kN	Min :	1.76	kN	Punch NO.;	25
SD :	0.60	%	Max :	1.82	kN	Punch NO.;	9
Mean Main Pressure :	14.78	kN	Min :	13.47	kN	Punch NO.;	36
SD :	3.20	%	Max :	15.79	kN	Punch NO.;	73
Filling Depth :	Increase ;	7	Times	Decrease ;	86	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.98	mm	Main Thickness ;	1.98	mm
Filling Depth :	6.21	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.32	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2952162	Tablets			
A.W.C Counter :	2943430	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2943430 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503150
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 17 Sec
Total Counter :	2952162	Total Running Time :	2538 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	40	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	18.49	kN	No		
HEP :	23.0 %	17.77	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.74	kN	Yes	15	Times
Ref :		14.45	kN			
LCP :	2.0 %	14.16	kN	Yes	15	Times
LEP :	23.0 %	11.12	kN	Yes	10	Rotations 15 Tablets
LSP :	28.0 %	10.40	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.50	kN	Min :	1.45	kN	Punch NO.;	52
SD :	1.30	%	Max :	1.55	kN	Punch NO.;	38
Mean Main Pressure :	14.36	kN	Min :	13.43	kN	Punch NO.;	10
SD :	3.10	%	Max :	15.50	kN	Punch NO.;	73
Filling Depth :	Increase ;	17	Times	Decrease ;	38	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.04	mm	Main Thickness ;	2.04	mm
Filling Depth :	6.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.32	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2952162	Tablets			
A.W.C Counter :	2943430	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2943430 (100.0%)	Tablets			