

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503150
Print Interval :	50000 Tablets	Running Time :	12 Hour 46 Min 24 Sec
Total Counter :	3302274	Total Running Time :	2539 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	18.62	kN	No		
HEP :	23.0 %	17.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.84	kN	Yes 15	Times	
Ref :		14.55	kN			
LCP :	2.0 %	14.26	kN	Yes 15	Times	
LEP :	23.0 %	11.20	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	10.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.81	kN	Min :	1.75	kN	Punch NO.;	21
SD :	0.80	%	Max :	1.84	kN	Punch NO.;	59
Mean Main Pressure :	14.66	kN	Min :	13.30	kN	Punch NO.;	36
SD :	3.20	%	Max :	16.09	kN	Punch NO.;	69
Filling Depth :	Increase ;	10	Times	Decrease ;	88	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.01	mm
Filling Depth :	6.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.811	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.35	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3302274	Tablets			
A.W.C Counter :	3293549	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3293549 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503150
Print Interval :	50000 Tablets	Running Time :	12 Hour 46 Min 24 Sec
Total Counter :	3302274	Total Running Time :	2539 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	40	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	18.38	kN	No		
HEP :	23.0 %	17.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.65	kN	Yes 15	Times	
Ref :		14.36	kN			
LCP :	2.0 %	14.07	kN	Yes 15	Times	
LEP :	23.0 %	11.06	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	10.34	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.51	kN	Min :	1.45	kN	Punch NO.;	11
SD :	1.30	%	Max :	1.56	kN	Punch NO.;	24
Mean Main Pressure :	14.43	kN	Min :	13.41	kN	Punch NO.;	11
SD :	2.90	%	Max :	15.36	kN	Punch NO.;	46
Filling Depth :	Increase ;	18	Times	Decrease ;	39	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.06	mm
Filling Depth :	6.80	mm	Current Cam :	Cam B	
Main Air pressure :	0.811	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.31	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3302274	Tablets			
A.W.C Counter :	3293549	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3293549 (100.0%)	Tablets			