

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	rp98927	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	12 Hour 50 Min 00 Sec
Total Counter :	3323586	Total Running Time :	2562 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	16.08	kN	No		
HEP :	23.0 %	15.45	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.81	kN	Yes	15	Times
Ref :		12.56	kN			
LCP :	2.0 %	12.31	kN	Yes	15	Times
LEP :	23.0 %	9.67	kN	Yes	10	Rotations 15 Tablets
LSP :	28.0 %	9.04	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.87	kN	Punch NO.;	7
SD :	0.80	%	Max :	1.95	kN	Punch NO.;	69
Mean Main Pressure :	12.62	kN	Min :	11.87	kN	Punch NO.;	14
SD :	3.30	%	Max :	14.17	kN	Punch NO.;	69
Filling Depth :	Increase ;	29	Times	Decrease ;	43	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.95	mm	Main Thickness ;	1.96	mm
Filling Depth :	6.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.32	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3323586	Tablets			
A.W.C Counter :	3316819	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3316819 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	rp98927	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	12 Hour 50 Min 00 Sec
Total Counter :	3323586	Total Running Time :	2562 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	40	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	15.43	kN	No		
HEP :	23.0 %	14.83	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.30	kN	Yes 15	Times	
Ref :		12.06	kN			
LCP :	2.0 %	11.81	kN	Yes 15	Times	
LEP :	23.0 %	9.28	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	8.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.72	kN	Min :	1.68	kN	Punch NO.;	75
SD :	1.00	%	Max :	1.76	kN	Punch NO.;	15
Mean Main Pressure :	12.04	kN	Min :	11.15	kN	Punch NO.;	37
SD :	3.10	%	Max :	13.00	kN	Punch NO.;	12
Filling Depth :	Increase ;	35	Times	Decrease ;	42	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	6.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	23
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3323586	Tablets			
A.W.C Counter :	3316819	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	3316819 (100.0%)	Tablets			