

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | sj97904       | Batch NO. :          | SHM2503450              |
| Print Interval : | 50000 Tablets | Running Time :       | 13 Hour 54 Min 27 Sec   |
| Total Counter :  | 3602966       | Total Running Time : | 2586 Hour 16 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 36                | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |             | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |             | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 28.0 %      | 13.69             | kN      | No                 |              |           |
| HEP :                              | 23.0 %      | 13.15             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 10.91             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 10.69             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 10.48             | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 %      | 8.23              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 28.0 %      | 7.70              | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |               |       |               |       |    |            |    |
|----------------------|---------------|-------|---------------|-------|----|------------|----|
| Mean Pre Pressure :  | 1.91          | kN    | Min :         | 1.86  | kN | Punch NO.; | 23 |
| SD :                 | 0.90          | %     | Max :         | 1.95  | kN | Punch NO.; | 62 |
| Mean Main Pressure : | 10.65         | kN    | Min :         | 9.42  | kN | Punch NO.; | 23 |
| SD :                 | 3.90          | %     | Max :         | 11.73 | kN | Punch NO.; | 65 |
| Filling Depth :      | Increase ; 42 | Times | Decrease ; 40 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 10       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80    | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.01    | mm  | Main Thickness ; | 2.02     | mm           |
| Filling Depth :               | 6.29    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 33      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 24      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.31 | kN |             |    |
|                  | Max ;     | 0.41 | kN | Max Punch ; | 23 |
| Lower Punch :    | Average ; | 0.14 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 14 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 3602966             | Tablets |       |            |         |
| A.W.C Counter : | 3597472             | Tablets |       |            |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 358 (0.0%) | Tablets |
| GOOD :          | 3597114<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | sj97904       | Batch NO. :          | SHM2503450              |
| Print Interval : | 50000 Tablets | Running Time :       | 13 Hour 54 Min 27 Sec   |
| Total Counter :  | 3602966       | Total Running Time : | 2586 Hour 16 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 36                | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 28.0 % | 13.84             | kN      | No                 |              |           |
| HEP :                              | 23.0 % | 13.30             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 11.03             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 10.81             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 10.59             | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 % | 8.32              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 28.0 % | 7.78              | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.71       | kN | Min : | 1.66       | kN | Punch NO.; | 23 |
| SD :                 | 1.50       | %  | Max : | 1.80       | kN | Punch NO.; | 69 |
| Mean Main Pressure : | 10.89      | kN | Min : | 9.88       | kN | Punch NO.; | 26 |
| SD :                 | 4.00       | %  | Max : | 11.96      | kN | Punch NO.; | 31 |
| Filling Depth :      | Increase ; | 58 | Times | Decrease ; | 40 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 10       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80    | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.06    | mm  | Main Thickness ; | 2.07     | mm           |
| Filling Depth :               | 6.07    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 33      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 24      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.30 | kN |             |    |
|                  | Max ;     | 0.41 | kN | Max Punch ; | 22 |
| Lower Punch :    | Average ; | 0.14 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 14 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 3602966             | Tablets |       |            |         |
| A.W.C Counter : | 3597472             | Tablets |       |            |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 358 (0.0%) | Tablets |
| GOOD :          | 3597114<br>(100.0%) | Tablets |       |            |         |