

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	kp99540	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	18 Hour 44 Min 32 Sec
Total Counter :	4853920	Total Running Time :	2591 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	14.06	kN	No		
HEP :	23.0 %	13.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.21	kN	Yes 15	Times	
Ref :		10.99	kN			
LCP :	2.0 %	10.77	kN	Yes 15	Times	
LEP :	23.0 %	8.46	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.86	kN	Punch NO.;	17
SD :	0.90	%	Max :	1.95	kN	Punch NO.;	62
Mean Main Pressure :	11.01	kN	Min :	10.01	kN	Punch NO.;	57
SD :	3.50	%	Max :	12.15	kN	Punch NO.;	69
Filling Depth :	Increase ;	60	Times	Decrease ;	62	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.22	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.82	kN		
	Max ;	1.20	kN	Max Punch ;	11
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4853920	Tablets			
A.W.C Counter :	4848051	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	4847625 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	kp99540	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	18 Hour 44 Min 32 Sec
Total Counter :	4853920	Total Running Time :	2591 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	14.94	kN	No		
HEP :	23.0 %	14.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.91	kN	Yes 15	Times	
Ref :		11.68	kN			
LCP :	2.0 %	11.44	kN	Yes 15	Times	
LEP :	23.0 %	8.99	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	8.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.73	kN	Min :	1.66	kN	Punch NO.;	28
		1.30	%	Max :	1.80	kN	Punch NO.;	31
Mean Main Pressure :		11.56	kN	Min :	10.50	kN	Punch NO.;	26
	SD :	3.40	%	Max :	12.59	kN	Punch NO.;	31
Filling Depth :	Increase ;	78	Times	Decrease ;	60	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	6.04	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.82	kN		
	Max ;	1.18	kN	Max Punch ;	11
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4853920	Tablets			
A.W.C Counter :	4848051	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	4847625 (100.0%)	Tablets			