

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	kp99540	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	21 Hour 15 Min 24 Sec
Total Counter :	5504466	Total Running Time :	2593 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	15.27	kN	No		
HEP :	23.0 %	14.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.17	kN	Yes 15	Times	
Ref :		11.93	kN			
LCP :	2.0 %	11.69	kN	Yes 15	Times	
LEP :	23.0 %	9.19	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	8.59	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.95	kN	Min :	1.92	kN	Punch NO.;	13
SD :	0.80	%	Max :	2.00	kN	Punch NO.;	63
Mean Main Pressure :	12.01	kN	Min :	11.25	kN	Punch NO.;	14
SD :	3.80	%	Max :	13.15	kN	Punch NO.;	9
Filling Depth :	Increase ;	77	Times	Decrease ;	106	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.37	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.80	kN		
	Max ;	1.25	kN	Max Punch ;	33
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5504466	Tablets			
A.W.C Counter :	5498114	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	5497688 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	kp99540	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	21 Hour 15 Min 24 Sec
Total Counter :	5504466	Total Running Time :	2593 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	15.68	kN	No		
HEP :	23.0 %	15.06	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.49	kN	Yes	15	Times
Ref :		12.25	kN			
LCP :	2.0 %	12.00	kN	Yes	15	Times
LEP :	23.0 %	9.43	kN	Yes	10	Rotations 15 Tablets
LSP :	28.0 %	8.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.77	kN	Min :	1.71	kN	Punch NO.;	23
		1.60	%	Max :	1.85	kN	Punch NO.;	67
Mean Main Pressure :	SD :	12.25	kN	Min :	10.95	kN	Punch NO.;	23
		3.90	%	Max :	13.64	kN	Punch NO.;	69
Filling Depth :	Increase ;	80	Times	Decrease ;	76	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	6.15	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.80	kN		
	Max ;	1.23	kN	Max Punch ;	33
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5504466	Tablets			
A.W.C Counter :	5498191	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	5497765 (100.0%)	Tablets			