

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	am98755	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	07 Hour 31 Min 22 Sec
Total Counter :	700160	Total Running Time :	2616 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	284	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.79	kN	No		
HEP :	25.0 %	36.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.65	kN	Yes 15	Times	
Ref :		29.07	kN			
LCP :	2.0 %	28.49	kN	Yes 15	Times	
LEP :	25.0 %	21.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.37	kN	Punch NO.;	9
SD :	1.80	%	Max :	2.59	kN	Punch NO.;	35
Mean Main Pressure :	29.65	kN	Min :	26.53	kN	Punch NO.;	17
SD :	4.50	%	Max :	32.38	kN	Punch NO.;	50
Filling Depth :	Increase ;	301	Times	Decrease ;	276	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	43	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.35	mm
Filling Depth :	10.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	30
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	12
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700160	Tablets			
A.W.C Counter :	697877	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	697859 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	am98755	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	07 Hour 31 Min 22 Sec
Total Counter :	700160	Total Running Time :	2616 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	309	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.90	kN	No		
HEP :	25.0 %	38.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.31	kN	Yes 15	Times	
Ref :		30.69	kN			
LCP :	2.0 %	30.08	kN	Yes 15	Times	
LEP :	25.0 %	23.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.48	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.01	kN	Punch NO.;	9
SD :	2.60	%	Max :	2.33	kN	Punch NO.;	50
Mean Main Pressure :	31.54	kN	Min :	26.94	kN	Punch NO.;	9
SD :	5.70	%	Max :	34.73	kN	Punch NO.;	50
Filling Depth :	Increase ;	93	Times	Decrease ;	97	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.49	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.44	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	12
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700160	Tablets			
A.W.C Counter :	697877	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	697859 (100.0%)	Tablets			