

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	am98755	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 52 Sec
Total Counter :	1100270	Total Running Time :	2621 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	297	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.05	kN	No		
HEP :	25.0 %	38.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.42	kN	Yes 15	Times	
Ref :		30.81	kN			
LCP :	2.0 %	30.19	kN	Yes 15	Times	
LEP :	25.0 %	23.10	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.35	kN	Punch NO.;	9
SD :	2.20	%	Max :	2.62	kN	Punch NO.;	41
Mean Main Pressure :	30.21	kN	Min :	26.90	kN	Punch NO.;	9
SD :	4.80	%	Max :	33.27	kN	Punch NO.;	41
Filling Depth :	Increase ;	429	Times	Decrease ;	398	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.35	mm
Filling Depth :	10.93	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100270	Tablets			
A.W.C Counter :	1097974	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1097956 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	am98755	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 52 Sec
Total Counter :	1100270	Total Running Time :	2621 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	309	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.18	kN	No		
HEP :	25.0 %	38.63	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.53	kN	Yes 15	Times	
Ref :		30.91	kN			
LCP :	2.0 %	30.29	kN	Yes 15	Times	
LEP :	25.0 %	23.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	2.00	kN	Punch NO.;	10
SD :	3.10	%	Max :	2.29	kN	Punch NO.;	44
Mean Main Pressure :	30.75	kN	Min :	26.17	kN	Punch NO.;	21
SD :	7.10	%	Max :	35.35	kN	Punch NO.;	50
Filling Depth :	Increase ;	132	Times	Decrease ;	130	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.49	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.44	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.94	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100270	Tablets			
A.W.C Counter :	1097974	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1097956 (100.0%)	Tablets			