

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP600MG<br>STIU2C00 |
| User ID :        | pb97604       | Batch NO. :          | IUM2504360              |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 20 Min 34 Sec   |
| Total Counter :  | 300066        | Total Running Time : | 2656 Hour 59 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 387      | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 1350000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50       | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 34.69    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 33.36    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 27.22    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 26.69    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 26.15    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 20.02    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 18.68    | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |      |       |            |      |            |    |
|----------------------|------------|------|-------|------------|------|------------|----|
| Mean Pre Pressure :  | 2.70       | kN   | Min : | 2.56       | kN   | Punch NO.; | 12 |
| SD :                 | 2.10       | %    | Max : | 2.82       | kN   | Punch NO.; | 41 |
| Mean Main Pressure : | 26.76      | kN   | Min : | 24.45      | kN   | Punch NO.; | 17 |
| SD :                 | 4.00       | %    | Max : | 29.40      | kN   | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 1815 | Times | Decrease ; | 1763 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |                   |              |
|-------------------------------|---------|-----|------------------|-------------------|--------------|
| Disk Speed :                  | 15      | RPM | Capacity :       | 95400             | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 58                | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |                   |              |
| Pre Lower Punch Position ;    | 8.25    | mm  | Pre Thickness ;  | 5.26              | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |                   |              |
| Main Lower Punch Position ;   | 7.48    | mm  | Main Thickness ; | 4.49              | mm           |
| Filling Depth :               | 10.72   | mm  | Current Cam :    | Cam C<br>8.5-14mm |              |
| Main Air pressure :           | 0.829   | MPa |                  |                   |              |
| Oil Lubrication status :      |         |     |                  |                   |              |
| Upper Punch Remain Time (S1): | 1       | Min |                  |                   |              |
| Lower Punch Remain Time (S2): | 1       | Min |                  |                   |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |                   |              |
| Powder Status :               | Disable |     | Dust Collector : | Off               |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off               |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 16 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 26 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |           |         |
|-----------------|--------------------|---------|-------|-----------|---------|
| Total Counter : | 300066             | Tablets |       |           |         |
| A.W.C Counter : | 298513             | Tablets |       |           |         |
| HEP :           | 1 (0.0%)           | Tablets | LEP : | 46 (0.0%) | Tablets |
| GOOD :          | 298466<br>(100.0%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP600MG<br>STIU2C00 |
| User ID :        | pb97604       | Batch NO. :          | IUM2504360              |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 20 Min 34 Sec   |
| Total Counter :  | 300066        | Total Running Time : | 2656 Hour 59 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 387               | %       | Manual ;           | 23           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 1350000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 20                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 32.42             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 31.17             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 25.44             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 24.94             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 24.44             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 18.70             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 17.46             | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.26       | kN  | Min : | 2.13       | kN  | Punch NO.; | 9  |
| SD :                 | 2.40       | %   | Max : | 2.39       | kN  | Punch NO.; | 29 |
| Mean Main Pressure : | 24.68      | kN  | Min : | 22.13      | kN  | Punch NO.; | 15 |
| SD :                 | 5.10       | %   | Max : | 27.17      | kN  | Punch NO.; | 51 |
| Filling Depth :      | Increase ; | 767 | Times | Decrease ; | 619 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 15      | RPM | Capacity :       | 95400    | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 58       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 8.38    | mm  | Pre Thickness ;  | 5.39     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 7.60    | mm  | Main Thickness ; | 4.61     | mm           |
| Filling Depth :               | 10.43   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.829   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 1       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 1       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 16 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 26 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |           |         |
|-----------------|--------------------|---------|-------|-----------|---------|
| Total Counter : | 300066             | Tablets |       |           |         |
| A.W.C Counter : | 298513             | Tablets |       |           |         |
| HEP :           | 1 (0.0%)           | Tablets | LEP : | 46 (0.0%) | Tablets |
| GOOD :          | 298466<br>(100.0%) | Tablets |       |           |         |