

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	ps99585	Batch NO. :	IUM2504460
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 09 Sec
Total Counter :	200054	Total Running Time :	2670 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	250	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	28.09	kN	No		
HEP :	25.0 %	27.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.04	kN	Yes 15	Times	
Ref :		21.61	kN			
LCP :	2.0 %	21.18	kN	Yes 15	Times	
LEP :	25.0 %	16.21	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.84	kN	Min :	3.79	kN	Punch NO.;	29
SD :	0.80	%	Max :	3.99	kN	Punch NO.;	15
Mean Main Pressure :	21.60	kN	Min :	19.56	kN	Punch NO.;	35
SD :	3.40	%	Max :	23.09	kN	Punch NO.;	31
Filling Depth :	Increase ; 80	Times	Decrease ;	52	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	3.98	mm			
Pre Lower Punch Position ;	8.99	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	3.98	mm			
Main Lower Punch Position ;	8.42	mm	Main Thickness ;	4.44	mm
Filling Depth :	10.83	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.826	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200054	Tablets			
A.W.C Counter :	187532	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	131 (0.1%)	Tablets
GOOD :	187354 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	ps99585	Batch NO. :	IUM2504460
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 09 Sec
Total Counter :	200054	Total Running Time :	2670 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	220	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	27.97	kN	No		
HEP :	25.0 %	26.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.95	kN	Yes 15	Times	
Ref :		21.52	kN			
LCP :	2.0 %	21.09	kN	Yes 15	Times	
LEP :	25.0 %	16.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.85	kN	Min :	3.80	kN	Punch NO.;	20
SD :	0.70	%	Max :	3.94	kN	Punch NO.;	15
Mean Main Pressure :	21.52	kN	Min :	19.52	kN	Punch NO.;	43
SD :	5.20	%	Max :	25.31	kN	Punch NO.;	20
Filling Depth :	Increase ;	58	Times	Decrease ;	23	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	33	RPM
Pre Upper Punch Position ;	4.01	mm			
Pre Lower Punch Position ;	8.99	mm	Pre Thickness ;	4.98	mm
Main Upper Punch Position ;	3.98	mm			
Main Lower Punch Position ;	8.42	mm	Main Thickness ;	4.44	mm
Filling Depth :	9.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	2
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200054	Tablets			
A.W.C Counter :	187532	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	131 (0.1%)	Tablets
GOOD :	187354 (99.9%)	Tablets			