

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	sj97904	Batch NO. :	LCM2507250
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 54 Sec
Total Counter :	1070638	Total Running Time :	2721 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	49.20	kN	No		
HEP :	25.0 %	47.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	38.60	kN	Yes 15	Times	
Ref :		37.85	kN			
LCP :	2.0 %	37.09	kN	Yes 15	Times	
LEP :	25.0 %	28.39	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	26.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.31	kN	Min :	8.24	kN	Punch NO.;	41
SD :	0.40	%	Max :	8.41	kN	Punch NO.;	52
Mean Main Pressure :	38.05	kN	Min :	35.80	kN	Punch NO.;	38
SD :	2.60	%	Max :	41.21	kN	Punch NO.;	26
Filling Depth :	Increase ; 12	Times	Decrease ; 29	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.16	mm
Filling Depth :	8.21	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1070638	Tablets			
A.W.C Counter :	1069304	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1069304 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	sj97904	Batch NO. :	LCM2507250
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 54 Sec
Total Counter :	1070638	Total Running Time :	2721 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	168	%	Manual ;	52	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	47.28	kN	No		
HEP :	25.0 %	45.46	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	37.09	kN	Yes 15	Times	
Ref :		36.37	kN			
LCP :	2.0 %	35.64	kN	Yes 15	Times	
LEP :	25.0 %	27.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.32	kN	Min :	8.26	kN	Punch NO.;	19
SD :	0.30	%	Max :	8.39	kN	Punch NO.;	52
Mean Main Pressure :	36.43	kN	Min :	34.97	kN	Punch NO.;	44
SD :	2.20	%	Max :	38.49	kN	Punch NO.;	23
Filling Depth :	Increase ;	12	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.26	mm	Main Thickness ;	3.27	mm
Filling Depth :	8.23	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	33
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1070638	Tablets			
A.W.C Counter :	1069304	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1069304 (100.0%)	Tablets			