

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	pb97604	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	04 Hour 13 Min 39 Sec
Total Counter :	400088	Total Running Time :	2728 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	190	%	Manual ;	23	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1320000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.88	kN	No		
HEP :	25.0 %	45.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.79	kN	Yes 15	Times	
Ref :		36.06	kN			
LCP :	2.0 %	35.34	kN	Yes 15	Times	
LEP :	25.0 %	27.05	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.40	kN	Min :	8.31	kN	Punch NO.;	41
SD :	0.40	%	Max :	8.49	kN	Punch NO.;	25
Mean Main Pressure :	36.39	kN	Min :	34.54	kN	Punch NO.;	9
SD :	2.30	%	Max :	38.03	kN	Punch NO.;	7
Filling Depth :	Increase ;	23	Times	Decrease ;	46	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	8.39	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400088	Tablets			
A.W.C Counter :	398513	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398513 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	pb97604	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	04 Hour 13 Min 39 Sec
Total Counter :	400088	Total Running Time :	2728 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	168	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.07	kN	No		
HEP :	25.0 %	44.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.15	kN	Yes 15	Times	
Ref :		35.44	kN			
LCP :	2.0 %	34.73	kN	Yes 15	Times	
LEP :	25.0 %	26.58	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	24.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	8.39	kN	Min :	8.34	kN	Punch NO.;	15
		0.40	%	Max :	8.47	kN	Punch NO.;	33
Mean Main Pressure :		35.51	kN	Min :	33.59	kN	Punch NO.;	39
	SD :	2.80	%	Max :	39.30	kN	Punch NO.;	7
Filling Depth :	Increase ;	21	Times	Decrease ;	22	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.28	mm	Main Thickness ;	3.29	mm
Filling Depth :	8.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400088	Tablets			
A.W.C Counter :	398513	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398513 (100.0%)	Tablets			