

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	13 Hour 44 Min 20 Sec
Total Counter :	1300346	Total Running Time :	2737 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	190	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.98	kN	No		
HEP :	25.0 %	45.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.86	kN	Yes 15	Times	
Ref :		36.14	kN			
LCP :	2.0 %	35.42	kN	Yes 15	Times	
LEP :	25.0 %	27.10	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.30	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.37	kN	Min :	8.29	kN	Punch NO.;	41
SD :	0.40	%	Max :	8.45	kN	Punch NO.;	25
Mean Main Pressure :	36.36	kN	Min :	34.11	kN	Punch NO.;	46
SD :	2.20	%	Max :	37.81	kN	Punch NO.;	19
Filling Depth :	Increase ;	103	Times	Decrease ;	135	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	8.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	10
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300346	Tablets			
A.W.C Counter :	1298190	Tablets			
HEP :	0 (0%)	Tablets	LEP :	140 (0.0%)	Tablets
GOOD :	1298050 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	13 Hour 44 Min 20 Sec
Total Counter :	1300346	Total Running Time :	2737 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	168	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.19	kN	No		
HEP :	25.0 %	44.42	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.24	kN	Yes 15	Times	
Ref :		35.53	kN			
LCP :	2.0 %	34.82	kN	Yes 15	Times	
LEP :	25.0 %	26.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	24.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	8.37	kN	Min :	8.28	kN	Punch NO.;	19
		0.30	%	Max :	8.44	kN	Punch NO.;	44
Mean Main Pressure :	SD :	36.10	kN	Min :	34.45	kN	Punch NO.;	46
		2.40	%	Max :	38.37	kN	Punch NO.;	7
Filling Depth :	Increase ;	65	Times	Decrease ;	59	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.28	mm	Main Thickness ;	3.29	mm
Filling Depth :	8.33	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	10
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300346	Tablets			
A.W.C Counter :	1298190	Tablets			
HEP :	0 (0%)	Tablets	LEP :	140 (0.0%)	Tablets
GOOD :	1298050 (100.0%)	Tablets			