

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	07 Hour 34 Min 18 Sec
Total Counter :	1200500	Total Running Time :	2745 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.44	kN	No		
HEP :	25.0 %	11.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.76	kN	Yes 15	Times	
Ref :		9.57	kN			
LCP :	2.0 %	9.38	kN	Yes 15	Times	
LEP :	25.0 %	7.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.73	kN	Min :	1.70	kN	Punch NO.;	32
SD :	1.00	%	Max :	1.78	kN	Punch NO.;	36
Mean Main Pressure :	9.49	kN	Min :	8.90	kN	Punch NO.;	18
SD :	2.60	%	Max :	10.01	kN	Punch NO.;	26
Filling Depth :	Increase ;	272	Times	Decrease ;	315	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.01	mm
Filling Depth :	7.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	36
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	50
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1200500	Tablets			
A.W.C Counter :	1190501	Tablets			
HEP :	77 (0.0%)	Tablets	LEP :	140 (0.0%)	Tablets
GOOD :	1190284 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	07 Hour 34 Min 18 Sec
Total Counter :	1200500	Total Running Time :	2745 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.46	kN	No		
HEP :	25.0 %	11.02	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.99	kN	Yes 15	Times	
Ref :		8.82	kN			
LCP :	2.0 %	8.64	kN	Yes 15	Times	
LEP :	25.0 %	6.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.37	kN	Min :	1.32	kN	Punch NO.;	1
SD :	2.10	%	Max :	1.45	kN	Punch NO.;	8
Mean Main Pressure :	8.88	kN	Min :	8.50	kN	Punch NO.;	1
SD :	2.70	%	Max :	9.73	kN	Punch NO.;	8
Filling Depth :	Increase ; 293	Times	Decrease ;	302	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.65	mm	Pre Thickness ;	3.66	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.24	mm	Main Thickness ;	3.25	mm
Filling Depth :	7.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	10
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	50
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1200500	Tablets			
A.W.C Counter :	1190554	Tablets			
HEP :	77 (0.0%)	Tablets	LEP :	140 (0.0%)	Tablets
GOOD :	1190337 (100.0%)	Tablets			