

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	01 Hour 23 Min 44 Sec
Total Counter :	4051704	Total Running Time :	2763 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.54	kN	No		
HEP :	25.0 %	13.02	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.63	kN	Yes 15	Times	
Ref :		10.42	kN			
LCP :	2.0 %	10.21	kN	Yes 15	Times	
LEP :	25.0 %	7.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.87	kN	Min :	1.81	kN	Punch NO.;	48
SD :	1.10	%	Max :	1.92	kN	Punch NO.;	33
Mean Main Pressure :	10.15	kN	Min :	9.37	kN	Punch NO.;	44
SD :	3.50	%	Max :	10.97	kN	Punch NO.;	22
Filling Depth :	Increase ; 685	Times	Decrease ;	735	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.93	mm	Main Thickness ;	2.94	mm
Filling Depth :	7.80	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	34
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4051704	Tablets			
A.W.C Counter :	4040372	Tablets			
HEP :	114 (0.0%)	Tablets	LEP :	424 (0.0%)	Tablets
GOOD :	4039834 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	01 Hour 23 Min 44 Sec
Total Counter :	4051704	Total Running Time :	2763 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.57	kN	No		
HEP :	25.0 %	12.09	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.86	kN	Yes 15	Times	
Ref :		9.67	kN			
LCP :	2.0 %	9.48	kN	Yes 15	Times	
LEP :	25.0 %	7.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.70	kN	Min :	1.57	kN	Punch NO.;	14
		2.30	%	Max :	1.80	kN	Punch NO.;	28
Mean Main Pressure :		10.22	kN	Min :	9.56	kN	Punch NO.;	39
	SD :	3.50	%	Max :	11.23	kN	Punch NO.;	28
Filling Depth :	Increase ;	778	Times	Decrease ;	792	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.813	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	34
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4051704	Tablets			
A.W.C Counter :	4040372	Tablets			
HEP :	114 (0.0%)	Tablets	LEP :	424 (0.0%)	Tablets
GOOD :	4039834 (100.0%)	Tablets			