

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500MG STMR2A00    |
| User ID :        | pb97604       | Batch NO. :          | MRM2502950            |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 35 Min 41 Sec |
| Total Counter :  | 4401824       | Total Running Time : | 2765 Hour 22 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 106      | %       | Manual ;           | 23           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 4500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50       | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 12.87    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 12.38    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 10.10    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 9.90     | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 9.71     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 7.43     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 6.93     | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.87       | kN  | Min : | 1.81       | kN  | Punch NO.; | 27 |
| SD :                 | 1.40       | %   | Max : | 1.95       | kN  | Punch NO.; | 29 |
| Mean Main Pressure : | 9.79       | kN  | Min : | 9.09       | kN  | Punch NO.; | 27 |
| SD :                 | 3.60       | %   | Max : | 10.90      | kN  | Punch NO.; | 29 |
| Filling Depth :      | Increase ; | 744 | Times | Decrease ; | 794 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |                   |              |
|-------------------------------|---------|-----|------------------|-------------------|--------------|
| Disk Speed :                  | 25      | RPM | Capacity :       | 159000            | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 26                | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |                   |              |
| Pre Lower Punch Position ;    | 6.60    | mm  | Pre Thickness ;  | 3.61              | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |                   |              |
| Main Lower Punch Position ;   | 6.00    | mm  | Main Thickness ; | 3.01              | mm           |
| Filling Depth :               | 7.83    | mm  | Current Cam :    | Cam C<br>8.5-14mm |              |
| Main Air pressure :           | 0.818   | MPa |                  |                   |              |
| Oil Lubrication status :      |         |     |                  |                   |              |
| Upper Punch Remain Time (S1): | 5       | Min |                  |                   |              |
| Lower Punch Remain Time (S2): | 14      | Min |                  |                   |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |                   |              |
| Powder Status :               | Disable |     | Dust Collector : | Off               |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off               |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 34 |
| Lower Punch :    | Average ; | 0.10 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 38 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 4401824             | Tablets |       |            |         |
| A.W.C Counter : | 4390490             | Tablets |       |            |         |
| HEP :           | 114 (0.0%)          | Tablets | LEP : | 424 (0.0%) | Tablets |
| GOOD :          | 4389952<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500MG STMR2A00    |
| User ID :        | pb97604       | Batch NO. :          | MRM2502950            |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 35 Min 41 Sec |
| Total Counter :  | 4401824       | Total Running Time : | 2765 Hour 22 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 103      | %       | Manual ;           | 26           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 4500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50       | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 12.05    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 11.59    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 9.46     | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 9.27     | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 9.09     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 6.95     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 6.49     | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N           |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.75       | kN  | Min : | 1.66       | kN  | Punch NO.; | 13 |
| SD :                 | 2.30       | %   | Max : | 1.87       | kN  | Punch NO.; | 33 |
| Mean Main Pressure : | 9.29       | kN  | Min : | 8.68       | kN  | Punch NO.; | 13 |
| SD :                 | 3.30       | %   | Max : | 10.36      | kN  | Punch NO.; | 28 |
| Filling Depth :      | Increase ; | 836 | Times | Decrease ; | 848 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25      | RPM | Capacity :       | 159000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 26       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.30    | mm  | Pre Thickness ;  | 3.31     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.21    | mm  | Main Thickness ; | 3.22     | mm           |
| Filling Depth :               | 7.86    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.818   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 5       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 14      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.13 | kN | Max Punch ; | 34 |
| Lower Punch :    | Average ; | 0.10 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 38 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                  |         |       |            |         |
|-----------------|------------------|---------|-------|------------|---------|
| Total Counter : | 4401824          | Tablets |       |            |         |
| A.W.C Counter : | 4390490          | Tablets |       |            |         |
| HEP :           | 114 (0.0%)       | Tablets | LEP : | 424 (0.0%) | Tablets |
| GOOD :          | 4389952 (100.0%) | Tablets |       |            |         |