

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	rk99163	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	04 Hour 43 Min 07 Sec
Total Counter :	750536	Total Running Time :	2770 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.59	kN	No		
HEP :	25.0 %	11.14	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.09	kN	Yes 15	Times	
Ref :		8.92	kN			
LCP :	2.0 %	8.74	kN	Yes 15	Times	
LEP :	25.0 %	6.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.78	kN	Punch NO.;	39
SD :	1.40	%	Max :	1.90	kN	Punch NO.;	10
Mean Main Pressure :	8.95	kN	Min :	8.20	kN	Punch NO.;	53
SD :	3.40	%	Max :	9.75	kN	Punch NO.;	29
Filling Depth :	Increase ; 10	Times	Decrease ; 14	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.99	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.64	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.737	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	39
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.10	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750536	Tablets			
A.W.C Counter :	745430	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	745355 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	rk99163	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	04 Hour 43 Min 07 Sec
Total Counter :	750536	Total Running Time :	2770 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.12	kN	No		
HEP :	25.0 %	10.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.72	kN	Yes 15	Times	
Ref :		8.55	kN			
LCP :	2.0 %	8.38	kN	Yes 15	Times	
LEP :	25.0 %	6.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.66	kN	Min :	1.59	kN	Punch NO.;	4
SD :	2.50	%	Max :	1.76	kN	Punch NO.;	35
Mean Main Pressure :	8.39	kN	Min :	7.94	kN	Punch NO.;	44
SD :	3.20	%	Max :	9.24	kN	Punch NO.;	28
Filling Depth :	Increase ; 9	Times	Decrease ; 9	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.20	mm	Main Thickness ;	3.21	mm
Filling Depth :	7.69	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.737	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	9
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.10	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750536	Tablets			
A.W.C Counter :	745430	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	745355 (100.0%)	Tablets			