

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	06 Hour 20 Min 21 Sec
Total Counter :	1000632	Total Running Time :	2772 Hour 14 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.59	kN	No		
HEP :	25.0 %	11.14	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.09	kN	Yes 15	Times	
Ref :		8.92	kN			
LCP :	2.0 %	8.74	kN	Yes 15	Times	
LEP :	25.0 %	6.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.79	kN	Punch NO.;	5
SD :	1.40	%	Max :	1.91	kN	Punch NO.;	21
Mean Main Pressure :	8.88	kN	Min :	8.16	kN	Punch NO.;	39
SD :	4.30	%	Max :	9.96	kN	Punch NO.;	32
Filling Depth :	Increase ; 40	Times	Decrease ;	47	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.99	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.697	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1000632	Tablets			
A.W.C Counter :	995378	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	995302 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	06 Hour 20 Min 21 Sec
Total Counter :	1000632	Total Running Time :	2772 Hour 14 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.12	kN	No		
HEP :	25.0 %	10.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.72	kN	Yes 15	Times	
Ref :		8.55	kN			
LCP :	2.0 %	8.38	kN	Yes 15	Times	
LEP :	25.0 %	6.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.65	kN	Min :	1.57	kN	Punch NO.;	48
SD :	2.30	%	Max :	1.74	kN	Punch NO.;	28
Mean Main Pressure :	8.54	kN	Min :	7.95	kN	Punch NO.;	27
SD :	3.60	%	Max :	9.24	kN	Punch NO.;	30
Filling Depth :	Increase ; 32	Times	Decrease ;	32	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.20	mm	Main Thickness ;	3.21	mm
Filling Depth :	7.69	mm	Current Cam :	Cam C	
Main Air pressure :	0.697	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1000632	Tablets			
A.W.C Counter :	995378	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	995302 (100.0%)	Tablets			