

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2503350
Print Interval :	50000 Tablets	Running Time :	13 Hour 13 Min 05 Sec
Total Counter :	1850668	Total Running Time :	2810 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	130	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.36	kN	No		
HEP :	25.0 %	12.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.49	kN	Yes 15	Times	
Ref :		10.28	kN			
LCP :	2.0 %	10.07	kN	Yes 15	Times	
LEP :	25.0 %	7.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.20	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.81	kN	Punch NO.;	5
SD :	1.80	%	Max :	1.98	kN	Punch NO.;	30
Mean Main Pressure :	10.42	kN	Min :	9.76	kN	Punch NO.;	5
SD :	4.30	%	Max :	11.79	kN	Punch NO.;	30
Filling Depth :	Increase ;	428	Times	Decrease ;	503	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.96	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.770	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1850668	Tablets			
A.W.C Counter :	1849293	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1849278 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2503350
Print Interval :	50000 Tablets	Running Time :	13 Hour 13 Min 05 Sec
Total Counter :	1850668	Total Running Time :	2810 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	130	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.59	kN	No		
HEP :	25.0 %	14.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.44	kN	Yes 15	Times	
Ref :		11.22	kN			
LCP :	2.0 %	11.00	kN	Yes 15	Times	
LEP :	25.0 %	8.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.87	kN	Punch NO.;	5
SD :	3.00	%	Max :	2.13	kN	Punch NO.;	28
Mean Main Pressure :	11.26	kN	Min :	10.15	kN	Punch NO.;	39
SD :	4.30	%	Max :	12.59	kN	Punch NO.;	28
Filling Depth :	Increase ;	518	Times	Decrease ;	543	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.25	mm	Pre Thickness ;	3.25	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.12	mm	Main Thickness ;	3.12	mm
Filling Depth :	7.67	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.770	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1850668	Tablets			
A.W.C Counter :	1849293	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1849278 (100.0%)	Tablets			