

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	rp98927	Batch NO. :	MRM2503350
Print Interval :	50000 Tablets	Running Time :	22 Hour 36 Min 14 Sec
Total Counter :	3201184	Total Running Time :	2819 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	122	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.11	kN	No		
HEP :	25.0 %	13.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.07	kN	Yes 15	Times	
Ref :		10.85	kN			
LCP :	2.0 %	10.64	kN	Yes 15	Times	
LEP :	25.0 %	8.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.60	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.89	kN	Punch NO.;	6
SD :	1.80	%	Max :	2.10	kN	Punch NO.;	28
Mean Main Pressure :	10.94	kN	Min :	10.31	kN	Punch NO.;	18
SD :	3.50	%	Max :	12.53	kN	Punch NO.;	28
Filling Depth :	Increase ;	474	Times	Decrease ;	561	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.95	mm
Filling Depth :	7.49	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	26
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3201184	Tablets			
A.W.C Counter :	3199564	Tablets			
HEP :	119 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	3199443	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	rp98927	Batch NO. :	MRM2503350
Print Interval :	50000 Tablets	Running Time :	22 Hour 36 Min 14 Sec
Total Counter :	3201184	Total Running Time :	2819 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	122	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.40	kN	No		
HEP :	25.0 %	13.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.30	kN	Yes 15	Times	
Ref :		11.08	kN			
LCP :	2.0 %	10.86	kN	Yes 15	Times	
LEP :	25.0 %	8.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.75	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.80	kN	Punch NO.;	6
SD :	3.10	%	Max :	2.15	kN	Punch NO.;	28
Mean Main Pressure :	11.12	kN	Min :	10.45	kN	Punch NO.;	17
SD :	4.40	%	Max :	12.94	kN	Punch NO.;	28
Filling Depth :	Increase ; 550	Times	Decrease ;	579	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.25	mm	Pre Thickness ;	3.25	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.12	mm	Main Thickness ;	3.12	mm
Filling Depth :	7.67	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	24
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3201184	Tablets			
A.W.C Counter :	3199617	Tablets			
HEP :	119 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	3199496 (100.0%)	Tablets			