

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 58 Sec
Total Counter :	45658	Total Running Time :	2842 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	16.50	kN	No		
HEP :	25.0 %	15.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.95	kN	Yes 15	Times	
Ref :		12.69	kN			
LCP :	2.0 %	12.44	kN	Yes 15	Times	
LEP :	25.0 %	9.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.88	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.47	kN	Punch NO.;	21
SD :	0.60	%	Max :	1.51	kN	Punch NO.;	17
Mean Main Pressure :	12.44	kN	Min :	11.14	kN	Punch NO.;	22
SD :	5.20	%	Max :	14.44	kN	Punch NO.;	16
Filling Depth :	Increase ; 3	Times	Decrease ; 5	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.697	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	46	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	61
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.31	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	45658	Tablets			
A.W.C Counter :	38125	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	38116 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 58 Sec
Total Counter :	45658	Total Running Time :	2842 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	15.41	kN	No		
HEP :	25.0 %	14.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.09	kN	Yes 15	Times	
Ref :		11.85	kN			
LCP :	2.0 %	11.61	kN	Yes 15	Times	
LEP :	25.0 %	8.89	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.30	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.09	kN	Min :	1.06	kN	Punch NO.;	1
SD :	0.80	%	Max :	1.11	kN	Punch NO.;	8
Mean Main Pressure :	11.78	kN	Min :	10.09	kN	Punch NO.;	75
SD :	8.50	%	Max :	14.25	kN	Punch NO.;	71
Filling Depth :	Increase ; 3	Times	Decrease ; 4	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	1.40	mm
Filling Depth :	4.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.697	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	46	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	61
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	45658	Tablets			
A.W.C Counter :	38125	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	38116 (100.0%)	Tablets			