

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | Panto 20 mg,STKQ1A00  |
| User ID :        | rp98927       | Batch NO. :          | KQM2503320            |
| Print Interval : | 50000 Tablets | Running Time :       | 09 Hour 45 Min 31 Sec |
| Total Counter :  | 2251228       | Total Running Time : | 2852 Hour 11 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 29       | %       | Manual ;           | 23           | RPM       |
| Filling Cam :                      |             | Cam B    |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |             | 4.5-10mm |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |             | 5500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50       | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 60       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 17.27    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 16.61    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 13.55    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 13.29    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 13.02    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 9.96     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 9.30     | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |               |       |            |       |       |            |    |
|----------------------|---------------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | 1.46          | kN    | Min :      | 1.45  | kN    | Punch NO.; | 7  |
| SD :                 | 0.40          | %     | Max :      | 1.49  | kN    | Punch NO.; | 73 |
| Mean Main Pressure : | 13.29         | kN    | Min :      | 10.33 | kN    | Punch NO.; | 49 |
| SD :                 | 8.10          | %     | Max :      | 16.15 | kN    | Punch NO.; | 42 |
| Filling Depth :      | Increase ; 87 | Times | Decrease ; | 118   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25      | RPM | Capacity :       | 231000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 7        | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.00    | mm  | Pre Thickness ;  | 2.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.22    | mm  | Main Thickness ; | 1.22     | mm           |
| Filling Depth :               | 4.27    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.816   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 26      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 16      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.01 | kN |             |    |
|                  | Max ;     | 0.04 | kN | Max Punch ; | 44 |
| Lower Punch :    | Average ; | 0.15 | kN |             |    |
|                  | Max ;     | 0.26 | kN | Max Punch ; | 45 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |            |         |
|-----------------|--------------------|---------|-------|------------|---------|
| Total Counter : | 2251228            | Tablets |       |            |         |
| A.W.C Counter : | 2240604            | Tablets |       |            |         |
| HEP :           | 1099 (0.0%)        | Tablets | LEP : | 444 (0.0%) | Tablets |
| GOOD :          | 2239061<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | Panto 20 mg,STKQ1A00  |
| User ID :        | rp98927       | Batch NO. :          | KQM2503320            |
| Print Interval : | 50000 Tablets | Running Time :       | 09 Hour 45 Min 31 Sec |
| Total Counter :  | 2251228       | Total Running Time : | 2852 Hour 11 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 34        | %       | Manual ;           | 27           | RPM       |
| Filling Cam :                      |        | Cam B     |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |        | 4.5-10mm  |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |        | 5500000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50        | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 60        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 17.73     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 17.05     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 13.91     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 13.64     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 13.37     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 10.23     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 9.55      | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.03       | kN  | Min : | 1.00       | kN  | Punch NO.; | 23 |
| SD :                 | 0.90       | %   | Max : | 1.05       | kN  | Punch NO.; | 15 |
| Mean Main Pressure : | 13.97      | kN  | Min : | 11.47      | kN  | Punch NO.; | 17 |
| SD :                 | 8.20       | %   | Max : | 16.84      | kN  | Punch NO.; | 38 |
| Filling Depth :      | Increase ; | 471 | Times | Decrease ; | 483 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25      | RPM | Capacity :       | 231000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 8        | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 4.90    | mm  | Pre Thickness ;  | 1.90     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.37    | mm  | Main Thickness ; | 1.37     | mm           |
| Filling Depth :               | 4.75    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.816   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 26      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 16      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.01 | kN |             |    |
|                  | Max ;     | 0.04 | kN | Max Punch ; | 51 |
| Lower Punch :    | Average ; | 0.15 | kN |             |    |
|                  | Max ;     | 0.26 | kN | Max Punch ; | 45 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |            |         |
|-----------------|--------------------|---------|-------|------------|---------|
| Total Counter : | 2251228            | Tablets |       |            |         |
| A.W.C Counter : | 2240604            | Tablets |       |            |         |
| HEP :           | 1099 (0.0%)        | Tablets | LEP : | 444 (0.0%) | Tablets |
| GOOD :          | 2239061<br>(99.9%) | Tablets |       |            |         |