

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	13 Hour 13 Min 17 Sec
Total Counter :	3051784	Total Running Time :	2855 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.27	kN	No		
HEP :	25.0 %	16.61	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.55	kN	Yes 15	Times	
Ref :		13.29	kN			
LCP :	2.0 %	13.02	kN	Yes 15	Times	
LEP :	25.0 %	9.96	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.30	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.43	kN	Min :	1.41	kN	Punch NO.;	1
SD :	0.50	%	Max :	1.45	kN	Punch NO.;	35
Mean Main Pressure :	13.23	kN	Min :	11.23	kN	Punch NO.;	10
SD :	7.40	%	Max :	15.70	kN	Punch NO.;	40
Filling Depth :	Increase ; 103	Times	Decrease ;	134	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.25	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	40
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.25	kN	Max Punch ;	64
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3051784	Tablets			
A.W.C Counter :	3039460	Tablets			
HEP :	1627 (0.1%)	Tablets	LEP :	825 (0.0%)	Tablets
GOOD :	3037008 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 3051784 Station : Station 2	Product Name : Panto 20 mg,STKQ1A00 Batch NO. : KQM2503320 Running Time : 13 Hour 13 Min 17 Sec Total Running Time : 2855 Hour 39 Min
---	--

Setting Value

Feeder :	Auto ;	38	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		5500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.46	kN	No		
HEP :	25.0 %	17.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.49	kN	Yes 15	Times	
Ref :		14.20	kN			
LCP :	2.0 %	13.92	kN	Yes 15	Times	
LEP :	25.0 %	10.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.00	kN	Min :	0.98	kN	Punch NO.;	26
		0.90	%	Max :	1.02	kN	Punch NO.;	22
Mean Main Pressure :		13.99	kN	Min :	11.15	kN	Punch NO.;	49
	SD :	7.10	%	Max :	16.31	kN	Punch NO.;	69
Filling Depth :	Increase ;	733	Times	Decrease ;	754	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.35	mm	Main Thickness ;	1.35	mm
Filling Depth :	4.69	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	40
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.25	kN	Max Punch ;	64
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3051784	Tablets			
A.W.C Counter :	3039537	Tablets			
HEP :	1627 (0.1%)	Tablets	LEP :	825 (0.0%)	Tablets
GOOD :	3037085 (99.9%)	Tablets			