

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	22 Hour 57 Min 46 Sec
Total Counter :	5303446	Total Running Time :	2865 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.37	kN	No		
HEP :	25.0 %	17.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.41	kN	Yes 15	Times	
Ref :		14.13	kN			
LCP :	2.0 %	13.85	kN	Yes 15	Times	
LEP :	25.0 %	10.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.89	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.41	kN	Min :	1.39	kN	Punch NO.;	59
SD :	0.50	%	Max :	1.42	kN	Punch NO.;	3
Mean Main Pressure :	14.38	kN	Min :	12.23	kN	Punch NO.;	37
SD :	6.60	%	Max :	16.91	kN	Punch NO.;	65
Filling Depth :	Increase ; 206	Times	Decrease ;	259	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.820	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	64
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	74
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5303446	Tablets			
A.W.C Counter :	5287569	Tablets			
HEP :	2595 (0.0%)	Tablets	LEP :	1484 (0.0%)	Tablets
GOOD :	5283490 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	22 Hour 57 Min 46 Sec
Total Counter :	5303446	Total Running Time :	2865 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	16.63	kN	No		
HEP :	25.0 %	15.99	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.04	kN	Yes 15	Times	
Ref :		12.79	kN			
LCP :	2.0 %	12.53	kN	Yes 15	Times	
LEP :	25.0 %	9.59	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	0.98	kN	Min :	0.95	kN	Punch NO.;	67
		1.10	%	Max :	1.01	kN	Punch NO.;	4
Mean Main Pressure :		13.09	kN	Min :	10.50	kN	Punch NO.;	1
	SD :	7.90	%	Max :	15.38	kN	Punch NO.;	58
Filling Depth :	Increase ;	1396	Times	Decrease ;	1399	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.35	mm	Main Thickness ;	1.35	mm
Filling Depth :	4.87	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.820	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	42
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	74
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5303446	Tablets			
A.W.C Counter :	5287569	Tablets			
HEP :	2595 (0.0%)	Tablets	LEP :	1484 (0.0%)	Tablets
GOOD :	5283490 (99.9%)	Tablets			