

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	01 Hour 13 Min 01 Sec
Total Counter :	224262	Total Running Time :	2866 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	33.63	kN	No		
HEP :	25.0 %	32.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.39	kN	Yes 15	Times	
Ref :		25.87	kN			
LCP :	2.0 %	25.35	kN	Yes 15	Times	
LEP :	25.0 %	19.40	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.11	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.85	kN	Min :	3.47	kN	Punch NO.;	5
SD :	4.80	%	Max :	4.28	kN	Punch NO.;	72
Mean Main Pressure :	26.02	kN	Min :	20.93	kN	Punch NO.;	44
SD :	6.40	%	Max :	29.84	kN	Punch NO.;	26
Filling Depth :	Increase ; 49	Times	Decrease ; 44	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.90	mm
Filling Depth :	4.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.770	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.35	kN	Max Punch ;	58
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.59	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	224262	Tablets			
A.W.C Counter :	188309	Tablets			
HEP :	144 (0.1%)	Tablets	LEP :	34 (0.0%)	Tablets
GOOD :	188131 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	01 Hour 13 Min 01 Sec
Total Counter :	224262	Total Running Time :	2866 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.95	kN	No		
HEP :	25.0 %	34.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.21	kN	Yes 15	Times	
Ref :		27.65	kN			
LCP :	2.0 %	27.10	kN	Yes 15	Times	
LEP :	25.0 %	20.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.36	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.04	kN	Min :	3.73	kN	Punch NO.;	50
SD :	4.10	%	Max :	4.52	kN	Punch NO.;	14
Mean Main Pressure :	27.92	kN	Min :	22.23	kN	Punch NO.;	44
SD :	5.00	%	Max :	31.01	kN	Punch NO.;	34
Filling Depth :	Increase ; 31	Times	Decrease ; 21	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.770	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.37	kN	Max Punch ;	66
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.59	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	224262	Tablets			
A.W.C Counter :	188309	Tablets			
HEP :	144 (0.1%)	Tablets	LEP :	34 (0.0%)	Tablets
GOOD :	188131 (99.9%)	Tablets			