

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	04 Hour 37 Min 20 Sec
Total Counter :	924734	Total Running Time :	2870 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.70	kN	No		
HEP :	25.0 %	37.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.37	kN	Yes 15	Times	
Ref :		29.77	kN			
LCP :	2.0 %	29.17	kN	Yes 15	Times	
LEP :	25.0 %	22.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.92	kN	Min :	3.51	kN	Punch NO.;	5
SD :	5.00	%	Max :	4.63	kN	Punch NO.;	75
Mean Main Pressure :	29.96	kN	Min :	25.21	kN	Punch NO.;	44
SD :	7.30	%	Max :	40.86	kN	Punch NO.;	37
Filling Depth :	Increase ;	142	Times	Decrease ;	156	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.27	kN	Max Punch ;	29
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.49	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	924734	Tablets			
A.W.C Counter :	885243	Tablets			
HEP :	250 (0.0%)	Tablets	LEP :	190 (0.0%)	Tablets
GOOD :	884803 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	04 Hour 37 Min 20 Sec
Total Counter :	924734	Total Running Time :	2870 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.94	kN	No		
HEP :	25.0 %	38.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.34	kN	Yes 15	Times	
Ref :		30.72	kN			
LCP :	2.0 %	30.11	kN	Yes 15	Times	
LEP :	25.0 %	23.04	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	4.05	kN	Min :	3.69	kN	Punch NO.;	19
		4.20	%	Max :	4.41	kN	Punch NO.;	2
Mean Main Pressure :	SD :	30.37	kN	Min :	18.85	kN	Punch NO.;	37
		6.10	%	Max :	33.65	kN	Punch NO.;	34
Filling Depth :	Increase ;	65	Times	Decrease ;	63	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.17	mm	Pre Thickness ;	1.17	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.78	mm	Main Thickness ;	0.78	mm
Filling Depth :	4.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.18	kN	Max Punch ;	17
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.49	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	924734	Tablets			
A.W.C Counter :	885243	Tablets			
HEP :	250 (0.0%)	Tablets	LEP :	190 (0.0%)	Tablets
GOOD :	884803 (100.0%)	Tablets			