

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	10 Hour 03 Min 31 Sec
Total Counter :	1925372	Total Running Time :	2875 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.59	kN	No		
HEP :	25.0 %	39.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.85	kN	Yes 15	Times	
Ref :		31.22	kN			
LCP :	2.0 %	30.60	kN	Yes 15	Times	
LEP :	25.0 %	23.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.89	kN	Min :	3.49	kN	Punch NO.;	60
		3.80	%	Max :	4.37	kN	Punch NO.;	14
Mean Main Pressure :	SD :	30.96	kN	Min :	26.07	kN	Punch NO.;	44
		4.80	%	Max :	34.37	kN	Punch NO.;	31
Filling Depth :	Increase ;	237	Times	Decrease ;	256	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.06	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.23	kN	Max Punch ;	5
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.43	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1925372	Tablets			
A.W.C Counter :	1884573	Tablets			
HEP :	273 (0.0%)	Tablets	LEP :	633 (0.0%)	Tablets
GOOD :	1883667 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	10 Hour 03 Min 31 Sec
Total Counter :	1925372	Total Running Time :	2875 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.76	kN	No		
HEP :	25.0 %	33.43	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.28	kN	Yes 15	Times	
Ref :		26.74	kN			
LCP :	2.0 %	26.21	kN	Yes 15	Times	
LEP :	25.0 %	20.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.05	kN	Min :	3.63	kN	Punch NO.;	16
SD :	4.20	%	Max :	4.50	kN	Punch NO.;	14
Mean Main Pressure :	26.71	kN	Min :	21.10	kN	Punch NO.;	44
SD :	5.10	%	Max :	30.20	kN	Punch NO.;	62
Filling Depth :	Increase ; 100	Times	Decrease ;	93	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.17	mm	Pre Thickness ;	1.17	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.90	mm
Filling Depth :	4.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.23	kN	Max Punch ;	5
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.41	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1925372	Tablets			
A.W.C Counter :	1884573	Tablets			
HEP :	273 (0.0%)	Tablets	LEP :	633 (0.0%)	Tablets
GOOD :	1883667 (100.0%)	Tablets			