

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	00 Hour 44 Min 29 Sec
Total Counter :	150104	Total Running Time :	2880 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.50	kN	No		
HEP :	25.0 %	37.02	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.21	kN	Yes 15	Times	
Ref :		29.62	kN			
LCP :	2.0 %	29.02	kN	Yes 15	Times	
LEP :	25.0 %	22.21	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.73	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.98	kN	Min :	3.65	kN	Punch NO.;	5
SD :	4.20	%	Max :	4.50	kN	Punch NO.;	14
Mean Main Pressure :	29.46	kN	Min :	25.42	kN	Punch NO.;	44
SD :	4.60	%	Max :	32.44	kN	Punch NO.;	26
Filling Depth :	Increase ;	448	Times	Decrease ;	465	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	3.29	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.748	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.26	kN	Max Punch ;	66
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.58	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150104	Tablets			
A.W.C Counter :	147446	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	24 (0.0%)	Tablets
GOOD :	147419 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	00 Hour 44 Min 29 Sec
Total Counter :	150104	Total Running Time :	2880 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.41	kN	No		
HEP :	25.0 %	35.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.35	kN	Yes 15	Times	
Ref :		28.78	kN			
LCP :	2.0 %	28.20	kN	Yes 15	Times	
LEP :	25.0 %	21.58	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.14	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.00	kN	Min :	3.69	kN	Punch NO.;	19
SD :	3.60	%	Max :	4.27	kN	Punch NO.;	56
Mean Main Pressure :	29.09	kN	Min :	25.28	kN	Punch NO.;	44
SD :	4.40	%	Max :	32.04	kN	Punch NO.;	46
Filling Depth :	Increase ; 200	Times	Decrease ;	189	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.76	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.748	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.26	kN	Max Punch ;	66
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.54	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150104	Tablets			
A.W.C Counter :	147446	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	24 (0.0%)	Tablets
GOOD :	147419 (100.0%)	Tablets			