

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 32 Sec
Total Counter :	1474750	Total Running Time :	2887 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.66	kN	No		
HEP :	25.0 %	37.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.33	kN	Yes 15	Times	
Ref :		29.74	kN			
LCP :	2.0 %	29.15	kN	Yes 15	Times	
LEP :	25.0 %	22.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.18	kN	Min :	3.85	kN	Punch NO.;	70
SD :	4.70	%	Max :	4.94	kN	Punch NO.;	14
Mean Main Pressure :	29.73	kN	Min :	23.57	kN	Punch NO.;	44
SD :	4.80	%	Max :	33.27	kN	Punch NO.;	34
Filling Depth :	Increase ; 51	Times	Decrease ; 57	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.19	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.28	kN	Max Punch ;	66
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.51	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1474750	Tablets			
A.W.C Counter :	1462776	Tablets			
HEP :	100 (0.0%)	Tablets	LEP :	899 (0.1%)	Tablets
GOOD :	1461777 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 32 Sec
Total Counter :	1474750	Total Running Time :	2887 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.75	kN	No		
HEP :	25.0 %	33.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.26	kN	Yes 15	Times	
Ref :		26.73	kN			
LCP :	2.0 %	26.19	kN	Yes 15	Times	
LEP :	25.0 %	20.05	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.98	kN	Min :	3.67	kN	Punch NO.;	6
		3.90	%	Max :	4.30	kN	Punch NO.;	49
Mean Main Pressure :		26.68	kN	Min :	23.20	kN	Punch NO.;	1
	SD :	4.70	%	Max :	29.28	kN	Punch NO.;	19
Filling Depth :	Increase ;	21	Times	Decrease ;	20	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.29	kN	Max Punch ;	66
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.51	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1474750	Tablets			
A.W.C Counter :	1462776	Tablets			
HEP :	100 (0.0%)	Tablets	LEP :	899 (0.1%)	Tablets
GOOD :	1461777 (99.9%)	Tablets			