

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	09 Hour 45 Min 27 Sec
Total Counter :	1975010	Total Running Time :	2889 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.10	kN	No		
HEP :	25.0 %	36.64	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.90	kN	Yes 15	Times	
Ref :		29.31	kN			
LCP :	2.0 %	28.72	kN	Yes 15	Times	
LEP :	25.0 %	21.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.52	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.13	kN	Min :	3.63	kN	Punch NO.;	5
SD :	4.30	%	Max :	4.67	kN	Punch NO.;	64
Mean Main Pressure :	29.11	kN	Min :	23.54	kN	Punch NO.;	44
SD :	5.40	%	Max :	33.90	kN	Punch NO.;	26
Filling Depth :	Increase ; 126	Times	Decrease ;	137	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.45	mm	Current Cam :	Cam B	
Main Air pressure :	0.814	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.28	kN	Max Punch ;	60
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.56	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1975010	Tablets			
A.W.C Counter :	1961487	Tablets			
HEP :	216 (0.0%)	Tablets	LEP :	990 (0.1%)	Tablets
GOOD :	1960281 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : sj97904 Print Interval : 50000 Tablets Total Counter : 1975010 Station : Station 2	Product Name : Panto 40 mg STKQ1B00 Batch NO. : KQM2509840 Running Time : 09 Hour 45 Min 27 Sec Total Running Time : 2889 Hour 52 Min
---	--

Setting Value

Feeder :	Auto ;	78	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		2750000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.82	kN	No		
HEP :	25.0 %	34.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.11	kN	Yes 15	Times	
Ref :		27.56	kN			
LCP :	2.0 %	27.00	kN	Yes 15	Times	
LEP :	25.0 %	20.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	4.09	kN	Min :	3.53	kN	Punch NO.;	5
		4.90	%	Max :	4.55	kN	Punch NO.;	14
Mean Main Pressure :		27.44	kN	Min :	21.90	kN	Punch NO.;	44
	SD :	4.70	%	Max :	30.29	kN	Punch NO.;	38
Filling Depth :	Increase ;	83	Times	Decrease ;	86	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.81	mm	Current Cam :	Cam B	
Main Air pressure :	0.814	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.30	kN	Max Punch ;	62
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.56	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1975010	Tablets			
A.W.C Counter :	1961487	Tablets			
HEP :	216 (0.0%)	Tablets	LEP :	990 (0.1%)	Tablets
GOOD :	1960281 (99.9%)	Tablets			