

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	os190259	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	11 Hour 29 Min 03 Sec
Total Counter :	2325228	Total Running Time :	2891 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.10	kN	No		
HEP :	25.0 %	36.64	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.90	kN	Yes 15	Times	
Ref :		29.31	kN			
LCP :	2.0 %	28.72	kN	Yes 15	Times	
LEP :	25.0 %	21.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.52	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.20	kN	Min :	3.72	kN	Punch NO.;	18
SD :	4.20	%	Max :	4.62	kN	Punch NO.;	10
Mean Main Pressure :	29.22	kN	Min :	22.90	kN	Punch NO.;	44
SD :	5.20	%	Max :	33.55	kN	Punch NO.;	34
Filling Depth :	Increase ;	179	Times	Decrease ;	187	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.30	kN	Max Punch ;	50
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.60	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2325228	Tablets			
A.W.C Counter :	2309591	Tablets			
HEP :	235 (0.0%)	Tablets	LEP :	1394 (0.1%)	Tablets
GOOD :	2307962 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	os190259	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	11 Hour 29 Min 03 Sec
Total Counter :	2325228	Total Running Time :	2891 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.82	kN	No		
HEP :	25.0 %	34.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.11	kN	Yes 15	Times	
Ref :		27.56	kN			
LCP :	2.0 %	27.00	kN	Yes 15	Times	
LEP :	25.0 %	20.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.13	kN	Min :	3.68	kN	Punch NO.;	5
SD :	4.20	%	Max :	4.56	kN	Punch NO.;	33
Mean Main Pressure :	27.25	kN	Min :	21.64	kN	Punch NO.;	44
SD :	5.80	%	Max :	31.02	kN	Punch NO.;	63
Filling Depth :	Increase ;	134	Times	Decrease ;	136	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.84	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.32	kN	Max Punch ;	76
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.60	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2325228	Tablets			
A.W.C Counter :	2309591	Tablets			
HEP :	235 (0.0%)	Tablets	LEP :	1394 (0.1%)	Tablets
GOOD :	2307962 (99.9%)	Tablets			