

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rk99163	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	06 Hour 51 Min 48 Sec
Total Counter :	1390270	Total Running Time :	2914 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.27	kN	No		
HEP :	25.0 %	32.95	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.89	kN	Yes 15	Times	
Ref :		26.36	kN			
LCP :	2.0 %	25.83	kN	Yes 15	Times	
LEP :	25.0 %	19.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.45	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.91	kN	Min :	3.38	kN	Punch NO.;	15
SD :	6.10	%	Max :	4.50	kN	Punch NO.;	2
Mean Main Pressure :	26.59	kN	Min :	22.01	kN	Punch NO.;	57
SD :	7.10	%	Max :	31.44	kN	Punch NO.;	76
Filling Depth :	Increase ; 23	Times	Decrease ; 10	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.82	mm
Filling Depth :	3.36	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.782	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.34	kN	Max Punch ;	66
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.54	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1390270	Tablets			
A.W.C Counter :	1378621	Tablets			
HEP :	300 (0.0%)	Tablets	LEP :	1927 (0.1%)	Tablets
GOOD :	1376394 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rk99163	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	06 Hour 51 Min 48 Sec
Total Counter :	1390270	Total Running Time :	2914 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.92	kN	No		
HEP :	25.0 %	33.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.40	kN	Yes 15	Times	
Ref :		26.86	kN			
LCP :	2.0 %	26.33	kN	Yes 15	Times	
LEP :	25.0 %	20.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.17	kN	Min :	3.48	kN	Punch NO.;	13
SD :	5.80	%	Max :	4.73	kN	Punch NO.;	45
Mean Main Pressure :	27.78	kN	Min :	23.19	kN	Punch NO.;	44
SD :	5.40	%	Max :	31.95	kN	Punch NO.;	7
Filling Depth :	Increase ; 14	Times	Decrease ; 17	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	3.78	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.782	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	26
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.54	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1390270	Tablets			
A.W.C Counter :	1378621	Tablets			
HEP :	300 (0.0%)	Tablets	LEP :	1927 (0.1%)	Tablets
GOOD :	1376394 (99.8%)	Tablets			