

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	am98755	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	10 Hour 16 Min 28 Sec
Total Counter :	2082100	Total Running Time :	2918 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.30	kN	No		
HEP :	25.0 %	35.86	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.26	kN	Yes 15	Times	
Ref :		28.69	kN			
LCP :	2.0 %	28.12	kN	Yes 15	Times	
LEP :	25.0 %	21.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.09	kN	Min :	3.69	kN	Punch NO.;	25
SD :	4.70	%	Max :	4.65	kN	Punch NO.;	42
Mean Main Pressure :	28.61	kN	Min :	21.86	kN	Punch NO.;	44
SD :	6.50	%	Max :	33.14	kN	Punch NO.;	26
Filling Depth :	Increase ; 52	Times	Decrease ; 42	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.82	mm
Filling Depth :	3.58	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.750	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.33	kN	Max Punch ;	60
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.48	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2082100	Tablets			
A.W.C Counter :	2068565	Tablets			
HEP :	443 (0.0%)	Tablets	LEP :	2293 (0.1%)	Tablets
GOOD :	2065829 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	am98755	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	10 Hour 16 Min 28 Sec
Total Counter :	2082100	Total Running Time :	2918 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.92	kN	No		
HEP :	25.0 %	33.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.40	kN	Yes 15	Times	
Ref :		26.86	kN			
LCP :	2.0 %	26.33	kN	Yes 15	Times	
LEP :	25.0 %	20.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.96	kN	Min :	3.49	kN	Punch NO.;	11
		4.90	%	Max :	4.73	kN	Punch NO.;	2
Mean Main Pressure :		26.65	kN	Min :	22.54	kN	Punch NO.;	44
	SD :	5.60	%	Max :	30.59	kN	Punch NO.;	34
Filling Depth :	Increase ;	24	Times	Decrease ;	20	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	3.75	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.750	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.37	kN	Max Punch ;	67
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.48	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2082100	Tablets			
A.W.C Counter :	2068565	Tablets			
HEP :	443 (0.0%)	Tablets	LEP :	2293 (0.1%)	Tablets
GOOD :	2065829 (99.9%)	Tablets			