

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	12 Hour 44 Min 25 Sec
Total Counter :	2582412	Total Running Time :	2920 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	41	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.04	kN	No		
HEP :	25.0 %	33.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.49	kN	Yes 15	Times	
Ref :		26.95	kN			
LCP :	2.0 %	26.41	kN	Yes 15	Times	
LEP :	25.0 %	20.21	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.12	kN	Min :	3.64	kN	Punch NO.;	5
SD :	4.30	%	Max :	4.62	kN	Punch NO.;	72
Mean Main Pressure :	27.17	kN	Min :	21.31	kN	Punch NO.;	57
SD :	6.60	%	Max :	31.93	kN	Punch NO.;	42
Filling Depth :	Increase ; 338	Times	Decrease ;	293	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	4.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.39	kN	Max Punch ;	66
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.45	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2582412	Tablets			
A.W.C Counter :	2567001	Tablets			
HEP :	573 (0.0%)	Tablets	LEP :	3009 (0.1%)	Tablets
GOOD :	2563419 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 2582412 Station : Station 2	Product Name : Panto 40 mg STKQ1B00 Batch NO. : KQM2510040 Running Time : 12 Hour 44 Min 25 Sec Total Running Time : 2920 Hour 41 Min
---	--

Setting Value

Feeder :	Auto ;	46	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.13	kN	No		
HEP :	25.0 %	34.74	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.35	kN	Yes 15	Times	
Ref :		27.79	kN			
LCP :	2.0 %	27.24	kN	Yes 15	Times	
LEP :	25.0 %	20.84	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.45	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	4.10	kN	Min :	3.62	kN	Punch NO.;	5
		5.20	%	Max :	4.71	kN	Punch NO.;	2
Mean Main Pressure :		27.43	kN	Min :	22.20	kN	Punch NO.;	44
	SD :	6.10	%	Max :	30.83	kN	Punch NO.;	26
Filling Depth :	Increase ;	71	Times	Decrease ;	60	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	4.10	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.39	kN	Max Punch ;	66
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.46	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2582412	Tablets			
A.W.C Counter :	2567001	Tablets			
HEP :	573 (0.0%)	Tablets	LEP :	3009 (0.1%)	Tablets
GOOD :	2563419 (99.9%)	Tablets			