

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	am98755	Batch NO. :	UBM2500420
Print Interval :	50000 Tablets	Running Time :	14 Hour 12 Min 54 Sec
Total Counter :	100018	Total Running Time :	2922 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	131	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.17	kN	No		
HEP :	25.0 %	17.47	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	14.32	kN	Yes 15	Times	
Ref :		13.97	kN			
LCP :	2.5 %	13.62	kN	Yes 15	Times	
LEP :	25.0 %	10.48	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.19	kN	Punch NO.;	15
SD :	0.40	%	Max :	2.25	kN	Punch NO.;	10
Mean Main Pressure :	13.84	kN	Min :	11.82	kN	Punch NO.;	11
SD :	8.90	%	Max :	16.84	kN	Punch NO.;	50
Filling Depth :	Increase ; 55	Times	Decrease ; 54	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.31	mm	Main Thickness ;	3.31	mm
Filling Depth :	8.30	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.716	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	44
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100018	Tablets			
A.W.C Counter :	89424	Tablets			
HEP :	565 (0.6%)	Tablets	LEP :	94 (0.1%)	Tablets
GOOD :	88765 (99.3%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	am98755	Batch NO. :	UBM2500420
Print Interval :	50000 Tablets	Running Time :	14 Hour 12 Min 54 Sec
Total Counter :	100018	Total Running Time :	2922 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.48	kN	No		
HEP :	25.0 %	17.77	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	14.57	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	2.5 %	13.86	kN	Yes 15	Times	
LEP :	25.0 %	10.66	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.18	kN	Punch NO.;	34
SD :	0.70	%	Max :	2.26	kN	Punch NO.;	27
Mean Main Pressure :	13.79	kN	Min :	12.51	kN	Punch NO.;	47
SD :	5.30	%	Max :	15.63	kN	Punch NO.;	35
Filling Depth :	Increase ;	55	Times	Decrease ;	53	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.716	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.19	kN	Max Punch ;	48
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100018	Tablets			
A.W.C Counter :	89424	Tablets			
HEP :	565 (0.6%)	Tablets	LEP :	94 (0.1%)	Tablets
GOOD :	88765 (99.3%)	Tablets			