

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	00 Hour 39 Min 03 Sec
Total Counter :	65568	Total Running Time :	2934 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	140	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	20.89	kN	No		
HEP :	25.0 %	20.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.47	kN	Yes 15	Times	
Ref :		16.07	kN			
LCP :	2.5 %	15.66	kN	Yes 15	Times	
LEP :	25.0 %	12.05	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.19	kN	Min :	2.17	kN	Punch NO.;	34
SD :	0.40	%	Max :	2.23	kN	Punch NO.;	10
Mean Main Pressure :	16.03	kN	Min :	14.19	kN	Punch NO.;	19
SD :	5.60	%	Max :	18.63	kN	Punch NO.;	10
Filling Depth :	Increase ; 258	Times	Decrease ;	278	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.27	mm	Main Thickness ;	3.27	mm
Filling Depth :	8.34	mm	Current Cam :	Cam C	
Main Air pressure :	0.772	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.25	kN	Max Punch ;	33
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	65568	Tablets			
A.W.C Counter :	57532	Tablets			
HEP :	358 (0.6%)	Tablets	LEP :	169 (0.3%)	Tablets
GOOD :	57005 (99.1%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	00 Hour 39 Min 03 Sec
Total Counter :	65568	Total Running Time :	2934 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.88	kN	No		
HEP :	25.0 %	18.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	14.89	kN	Yes 15	Times	
Ref :		14.52	kN			
LCP :	2.5 %	14.16	kN	Yes 15	Times	
LEP :	25.0 %	10.89	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	2.13	kN	Punch NO.;	7
SD :	0.60	%	Max :	2.19	kN	Punch NO.;	5
Mean Main Pressure :	14.30	kN	Min :	12.47	kN	Punch NO.;	13
SD :	5.90	%	Max :	15.76	kN	Punch NO.;	21
Filling Depth :	Increase ; 600	Times	Decrease ;	527	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.53	mm	Main Thickness ;	3.53	mm
Filling Depth :	8.98	mm	Current Cam :	Cam C	
				8.5-14mm	
Main Air pressure :	0.772	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.25	kN	Max Punch ;	33
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	65568	Tablets			
A.W.C Counter :	57532	Tablets			
HEP :	358 (0.6%)	Tablets	LEP :	169 (0.3%)	Tablets
GOOD :	57005 (99.1%)	Tablets			