

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 27 Sec
Total Counter :	350172	Total Running Time :	2936 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	21.34	kN	No		
HEP :	25.0 %	20.52	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.83	kN	Yes 15	Times	
Ref :		16.42	kN			
LCP :	2.5 %	16.01	kN	Yes 15	Times	
LEP :	25.0 %	12.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	2.14	kN	Punch NO.;	8
SD :	0.40	%	Max :	2.18	kN	Punch NO.;	1
Mean Main Pressure :	16.57	kN	Min :	15.04	kN	Punch NO.;	48
SD :	4.80	%	Max :	18.65	kN	Punch NO.;	32
Filling Depth :	Increase ; 438	Times	Decrease ;	428	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	34	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.27	mm	Main Thickness ;	3.27	mm
Filling Depth :	8.71	mm	Current Cam :	Cam C	
Main Air pressure :	0.676	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.26	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	32
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350172	Tablets			
A.W.C Counter :	341632	Tablets			
HEP :	847 (0.2%)	Tablets	LEP :	191 (0.1%)	Tablets
GOOD :	340594 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 27 Sec
Total Counter :	350172	Total Running Time :	2936 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	19.03	kN	No		
HEP :	25.0 %	18.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	15.01	kN	Yes 15	Times	
Ref :		14.64	kN			
LCP :	2.5 %	14.28	kN	Yes 15	Times	
LEP :	25.0 %	10.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.14	kN	Min :	2.11	kN	Punch NO.;	8
SD :	0.70	%	Max :	2.21	kN	Punch NO.;	53
Mean Main Pressure :	14.52	kN	Min :	13.19	kN	Punch NO.;	1
SD :	4.40	%	Max :	16.17	kN	Punch NO.;	41
Filling Depth :	Increase ;	781	Times	Decrease ;	675	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.53	mm	Main Thickness ;	3.53	mm
Filling Depth :	9.09	mm	Current Cam :	Cam C	
Main Air pressure :	0.676	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.26	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	32
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350172	Tablets			
A.W.C Counter :	341632	Tablets			
HEP :	847 (0.2%)	Tablets	LEP :	191 (0.1%)	Tablets
GOOD :	340594 (99.7%)	Tablets			