

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	00 Hour 30 Min 55 Sec
Total Counter :	100084	Total Running Time :	2946 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.30	kN	No		
HEP :	25.0 %	38.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	31.77	kN	Yes 15	Times	
Ref :		31.00	kN			
LCP :	2.5 %	30.22	kN	Yes 15	Times	
LEP :	25.0 %	23.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.98	kN	Min :	3.56	kN	Punch NO.;	55
SD :	5.20	%	Max :	4.57	kN	Punch NO.;	49
Mean Main Pressure :	31.36	kN	Min :	27.08	kN	Punch NO.;	52
SD :	4.10	%	Max :	34.36	kN	Punch NO.;	49
Filling Depth :	Increase ; 24	Times	Decrease ;	8	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	4.01	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.21	kN	Max Punch ;	5
Lower Punch :	Average ;	0.45	kN		
	Max ;	1.03	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100084	Tablets			
A.W.C Counter :	89032	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	89026 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	00 Hour 30 Min 55 Sec
Total Counter :	100084	Total Running Time :	2946 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.83	kN	No		
HEP :	25.0 %	37.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	30.62	kN	Yes 15	Times	
Ref :		29.87	kN			
LCP :	2.5 %	29.12	kN	Yes 15	Times	
LEP :	25.0 %	22.40	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.02	kN	Min :	3.65	kN	Punch NO.;	9
SD :	5.30	%	Max :	4.68	kN	Punch NO.;	50
Mean Main Pressure :	30.16	kN	Min :	24.88	kN	Punch NO.;	52
SD :	3.90	%	Max :	32.83	kN	Punch NO.;	51
Filling Depth :	Increase ;	1	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.77	mm	Main Thickness ;	0.77	mm
Filling Depth :	3.65	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	42
Lower Punch :	Average ;	0.45	kN		
	Max ;	1.03	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100084	Tablets			
A.W.C Counter :	89032	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	89026 (100.0%)	Tablets			