

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	02 Hour 49 Min 42 Sec
Total Counter :	550272	Total Running Time :	2949 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.10	kN	No		
HEP :	25.0 %	39.52	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	32.41	kN	Yes 15	Times	
Ref :		31.62	kN			
LCP :	2.5 %	30.83	kN	Yes 15	Times	
LEP :	25.0 %	23.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.20	kN	Min :	3.78	kN	Punch NO.;	75
SD :	5.30	%	Max :	4.84	kN	Punch NO.;	46
Mean Main Pressure :	32.12	kN	Min :	28.86	kN	Punch NO.;	52
SD :	4.00	%	Max :	35.08	kN	Punch NO.;	53
Filling Depth :	Increase ; 44	Times	Decrease ; 58	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.769	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	73
Lower Punch :	Average ;	0.46	kN		
	Max ;	0.83	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550272	Tablets			
A.W.C Counter :	533174	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	574 (0.1%)	Tablets
GOOD :	532528 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	02 Hour 49 Min 42 Sec
Total Counter :	550272	Total Running Time :	2949 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.70	kN	No		
HEP :	25.0 %	40.10	kN	Yes	10	Rotations 15 Tablets
HCP :	2.5 %	32.88	kN	Yes	15	Times
Ref :		32.08	kN			
LCP :	2.5 %	31.28	kN	Yes	15	Times
LEP :	25.0 %	24.06	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	22.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.22	kN	Min :	3.83	kN	Punch NO.;	22
SD :	4.90	%	Max :	4.82	kN	Punch NO.;	53
Mean Main Pressure :	32.05	kN	Min :	26.99	kN	Punch NO.;	52
SD :	4.00	%	Max :	34.78	kN	Punch NO.;	53
Filling Depth :	Increase ;	14	Times	Decrease ;	30	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.77	mm	Main Thickness ;	0.77	mm
Filling Depth :	3.88	mm	Current Cam :	Cam B	
Main Air pressure :	0.769	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.18	kN	Max Punch ;	5
Lower Punch :	Average ;	0.46	kN		
	Max ;	0.83	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550272	Tablets			
A.W.C Counter :	533174	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	574 (0.1%)	Tablets
GOOD :	532528 (99.9%)	Tablets			