

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 48 Sec
Total Counter :	700306	Total Running Time :	2949 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.10	kN	No		
HEP :	25.0 %	39.52	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	32.41	kN	Yes 15	Times	
Ref :		31.62	kN			
LCP :	2.5 %	30.83	kN	Yes 15	Times	
LEP :	25.0 %	23.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.94	kN	Min :	3.47	kN	Punch NO.;	17
		5.50	%	Max :	5.11	kN	Punch NO.;	38
Mean Main Pressure :	SD :	31.45	kN	Min :	24.58	kN	Punch NO.;	50
		5.50	%	Max :	40.58	kN	Punch NO.;	38
Filling Depth :	Increase ;	56	Times	Decrease ;	71	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.66	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.763	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.22	kN	Max Punch ;	29
Lower Punch :	Average ;	0.39	kN		
	Max ;	1.03	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700306	Tablets			
A.W.C Counter :	682946	Tablets			
HEP :	90 (0.0%)	Tablets	LEP :	593 (0.1%)	Tablets
GOOD :	682263 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 48 Sec
Total Counter :	700306	Total Running Time :	2949 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.70	kN	No		
HEP :	25.0 %	40.10	kN	Yes	10	Rotations 15 Tablets
HCP :	2.5 %	32.88	kN	Yes	15	Times
Ref :		32.08	kN			
LCP :	2.5 %	31.28	kN	Yes	15	Times
LEP :	25.0 %	24.06	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	22.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.02	kN	Min :	3.66	kN	Punch NO.;	71
SD :	5.90	%	Max :	5.47	kN	Punch NO.;	38
Mean Main Pressure :	31.86	kN	Min :	25.72	kN	Punch NO.;	50
SD :	4.90	%	Max :	40.65	kN	Punch NO.;	38
Filling Depth :	Increase ;	17	Times	Decrease ;	36	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.77	mm	Main Thickness ;	0.77	mm
Filling Depth :	3.79	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.763	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.22	kN	Max Punch ;	29
Lower Punch :	Average ;	0.39	kN		
	Max ;	1.02	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700306	Tablets			
A.W.C Counter :	682946	Tablets			
HEP :	90 (0.0%)	Tablets	LEP :	593 (0.1%)	Tablets
GOOD :	682263 (99.9%)	Tablets			